

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
2/26/24		6	ARK.	110706	1	45
BOAT GUNWALE SLASH STR. & APPRS. (S)						

ARKANSAS DEPARTMENT OF TRANSPORTATION
CONSTRUCTION PLANS FOR STATE HIGHWAY




**BOAT GUNWALE SLASH
STR. & APPRS. (S)**

MONROE COUNTY
ROUTE 17 SECTION 1

JOB 110706

FED. AID PROJ. BFP-NHPP-0048(39)


NOT TO SCALE



ARK. HWY. DIST. NO. 1

DESIGN TRAFFIC DATA


DESIGN YEAR	2044
2024 ADT	450
2044 ADT	530
2044 DHV	58
DIRECTIONAL DISTRIBUTION	0.60
TRUCKS	13%
DESIGN SPEED	55 MPH



VICINITY MAP

BRIDGE DATA

- ① STA. 106+91.50 BRIDGE END
BRIDGE NO. 07603
119'-0" PRECAST CONCRETE BEAM UNIT
(39.5'-40'-39.5')
30'-0" CLEAR ROADWAY
119'-0" TOTAL LENGTH
STA. 108+10.50 BRIDGE END
025 = 1620 CFS
& D.A. = 35.7 SQ. MI.



STA. 112+35.00
END JOB 110706



APPROVED




CHIEF ENGINEER - PRECONSTRUCTION

MAR 27 2024

	BEGIN PROJECT	MID-POINT OF PROJECT	END PROJECT
LATITUDE	N 34°32'52"	N 34°32'57"	N 34°33'02"
LONGITUDE	W 91°10'28"	W 91°10'27"	W 91°10'27"

LENGTH OF PROJECT CALCULATED ALONG C.L.			
	FEET	OR	MILES
GROSS LENGTH OF PROJECT	960.00		0.182
NET ROADWAY	841.00		0.159
NET BRIDGES	119.00		0.023
NET PROJECT	960.00		0.182

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	2	45
INDEX OF SHEETS AND STANDARD DRAWINGS						



INDEX OF SHEETS

SHEET NO.	TITLE	BRIDGE NO.	DRWG. NO.
1	TITLE SHEET		
2	INDEX OF SHEETS AND STANDARD DRAWINGS		
3	GOVERNING SPECIFICATIONS AND GENERAL NOTES		
4 - 5	TYPICAL SECTIONS OF IMPROVEMENT		
6 - 7	SPECIAL DETAILS		
8 - 11	TEMPORARY EROSION CONTROL DETAILS		
12 - 17	MAINTENANCE OF TRAFFIC DETAILS		
18	PERMANENT PAVEMENT MARKING DETAILS		
19 - 21	QUANTITIES		
22	SCHEDULE OF BRIDGE QUANTITIES	07603	65977
23	SUMMARY OF QUANTITIES AND REVISIONS		
24 - 26	SURVEY CONTROL DETAILS		
27 - 28	PLAN AND PROFILE SHEETS		
29	LAYOUT OF BRIDGE HIGHWAY 17 OVER BOAT GUNWALE SLASH (SHEET 1 OF 2)	07603	65978
30	LAYOUT OF BRIDGE HIGHWAY 17 OVER BOAT GUNWALE SLASH (SHEET 2 OF 2)	07603	65979
31	DETAILS OF END BENTS (SHEET 1 OF 2)	07603	65980
32	DETAILS OF END BENTS (SHEET 2 OF 2)	07603	65981
33	DETAILS OF INTERMEDIATE BENTS	07603	65982
34	DETAILS OF PRECAST PRESTRESSED BEAM UNIT (SHEET 1 OF 4)	07603	65983
35	DETAILS OF PRECAST PRESTRESSED BEAM UNIT (SHEET 2 OF 4)	07603	65984
36	DETAILS OF PRECAST PRESTRESSED BEAM UNIT (SHEET 3 OF 4)	07603	65985
37	DETAILS OF PRECAST PRESTRESSED BEAM UNIT (SHEET 4 OF 4)	07603	65986
38	DETAILS FOR TYPE SPECIAL APPROACH SLAB	07603	65987
39	DETAILS FOR TYPE SPECIAL APPROACH GUTTER	07603	65988
40 - 45	CROSS SECTIONS		

BRIDGE STANDARD DRAWINGS

DRWG. NO.	TITLE	DATE
55000	STANDARD DETAILS FOR EMBANKMENT CONSTRUCTION AND BACKFILL AT BRIDGE ENDS	02-27-14
55010	STANDARD DETAILS FOR TYPE D BRIDGE NAME PLATE	04-14-23
55021	STANDARD DETAILS FOR CONCRETE FILLED STEEL SHELL PILES AND PILE ENCASEMENTS	03-24-16
55040E	STANDARD DETAILS FOR TYPE E APPROACH SLAB	02-27-14
55070	STANDARD DETAILS FOR BRIDGE TRAFFIC RAIL TYPE SSSTR36	09-27-22

ROADWAY STANDARD DRAWINGS


DRWG. NO.	TITLE	DATE
DR-2	DETAILS OF DRIVEWAYS & STREET TURNOUTS	05-19-22
GR-6	GUARDRAIL DETAILS	05-19-22
GR-7	GUARDRAIL DETAILS	11-07-19
GR-8	GUARDRAIL DETAILS	11-07-19
GR-9	GUARDRAIL DETAILS	11-07-19
GR-10	GUARDRAIL DETAILS	11-07-19
GR-11	GUARDRAIL DETAILS	11-07-19
GR-12	GUARDRAIL DETAILS	05-14-20
PCC-1	CONCRETE PIPE CULVERT FILL HEIGHTS & BEDDING	02-27-14
PCM-1	METAL PIPE CULVERT FILL HEIGHTS & BEDDING	02-27-14
PCP-1	PLASTIC PIPE CULVERT (HIGH DENSITY POLYETHYLENE)	02-27-14
PCP-2	PLASTIC PIPE CULVERT (PVC F949)	02-27-14
PCP-3	PLASTIC PIPE CULVERT (POLYPROPYLENE)	02-27-20
PM-1	PAVEMENT MARKING DETAILS	02-27-20
PU-1	DETAILS OF PIPE UNDERDRAIN	12-08-16
SE-2	TABLES AND METHOD OF SUPERELEVATION FOR TWO-WAY TRAFFIC	11-07-19
TC-1	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION	11-07-19
TC-2	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION	05-20-21
TC-3	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION	08-12-21
TC-4	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION-TEMPORARY PRECAST BARRIER	11-07-19
TC-5	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION-TEMPORARY PRECAST BARRIER	11-07-19
TEC-1	TEMPORARY EROSION CONTROL DEVICES	11-16-17
TEC-3	TEMPORARY EROSION CONTROL DEVICES	11-03-94

GOVERNING SPECIFICATIONS

ARKANSAS STATE HIGHWAY COMMISSION STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION, EDITION OF 2014, AND THE FOLLOWING SPECIAL PROVISIONS AND SUPPLEMENTAL SPECIFICATIONS:

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
2/26/24		6	ARK.	110706	3	45
7/24/24						
9/4/24						

GOVERNING SPECS. AND GENERAL NOTES



NUMBER	TITLE
ERRATA	ERRATA FOR THE BOOK OF STANDARD SPECIFICATIONS
FHWA-1273	REQUIRED CONTRACT PROVISIONS FEDERAL-AID CONSTRUCTION CONTRACTS
FHWA-1273	SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - NOTICE TO CONTRACTORS
FHWA-1273	SUPPLEMENT - SPECIFIC EQUAL EMPLOYMENT OPPORTUNITY RESPONSIBILITIES (23 U.S.C. 140)
FHWA-1273	SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - GOALS AND TIMETABLES
FHWA-1273	SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - FEDERAL STANDARDS
FHWA-1273	SUPPLEMENT - POSTERS AND NOTICES REQUIRED FOR FEDERAL-AID PROJECTS
FHWA-1273	SUPPLEMENT - WAGE RATE DETERMINATION
100-3	CONTRACTOR'S LICENSE
100-4	DEPARTMENT NAME CHANGE
102-2	ISSUANCE OF PROPOSALS
102-3	PREQUALIFICATION OF BIDDERS
103-2	CONTACT INFORMATION FOR MOTORIST DAMAGE CLAIMS
105-4	MAINTENANCE DURING CONSTRUCTION
107-2	RESTRAINING CONDITIONS
108-1	LIQUIDATED DAMAGES
108-2	WORK ALLOWED PRIOR TO ISSUANCE OF WORK ORDER
110-1	PROTECTION OF WATER QUALITY AND WETLANDS
210-1	UNCLASSIFIED EXCAVATION
303-1	AGGREGATE BASE COURSE
306-1	QUALITY CONTROL AND ACCEPTANCE
307-2	CEMENT TREATED BASE COURSE
308-2	CEMENT STABILIZED CRUSHED STONE BASE COURSE
400-1	TACK COATS
400-4	DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES
400-5	PERCENT AIR VOIDS FOR ACHM MIX DESIGNS
400-6	LIQUID ANTI-STRIP ADDITIVE
400-7	TRACKLESS TACK
404-3	DESIGN OF ASPHALT MIXTURES
409-2	ASPHALT LABORATORY FACILITY
410-1	CONSTRUCTION REQUIREMENTS AND ACCEPTANCE OF ASPHALT CONCRETE PLANT MIX COURSES
410-2	DEVICES FOR MEASURING DENSITY FOR ROLLING PATTERNS
410-4	EVALUATION OF ACHM SUBLOT REPLACEMENT MATERIAL
416-1	RECYCLED ASPHALT PAVEMENT
501-3	PORTLAND CEMENT CONCRETE PAVEMENT
600-2	INCIDENTAL CONSTRUCTION
603-1	LANE CLOSURE NOTIFICATION
604-1	RETROREFLECTIVE SHEETING FOR TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES
604-3	TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES (MASH)
606-1	PIPE CULVERTS FOR SIDE DRAINS
617-1	GUARDRAIL TERMINAL (TYPE 2)
617-2	GUARDRAIL DELINEATORS
620-1	MULCH COVER
800-1	STRUCTURES
802-3	CONCRETE FOR STRUCTURES
802-5	CONCRETE FOR STRUCTURES
804-2	REINFORCING STEEL FOR STRUCTURES
JOB 110706	BIDDING REQUIREMENTS AND CONDITIONS
JOB 110706	BROADBAND INTERNET SERVICE FOR ASPHALT CONCRETE PLANT
JOB 110706	BROADBAND INTERNET SERVICE FOR FIELD OFFICE
JOB 110706	BUY AMERICA - CONSTRUCTION MATERIALS
JOB 110706	CARGO PREFERENCE ACT REQUIREMENTS
JOB 110706	CLASS C FLY ASH IN PORTLAND CEMENT CONCRETE PAVEMENT AND CLASS S(AE) CONCRETE
JOB 110706	COLD MILLING - COUNTY PROPERTY
JOB 110706	CONCRETE BRIDGE DECK CURING AND SURFACE TREATMENT RESTRICTIONS
JOB 110706	CONSTRUCTION IN SPECIAL FLOOD HAZARD AREAS
JOB 110706	DESIGN AND QUALITY CONTROL ASPHALT MIXTURES
JOB 110706	DISADVANTAGED BUSINESS ENTERPRISE BIDDER'S RESPONSIBILITIES
JOB 110706	FLEXIBLE BEGINNING OF WORK - CALENDAR DAY CONTRACT
JOB 110706	GOALS FOR DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION
JOB 110706	LIQUIDATED DAMAGES PROCEDURE FOR BID LETTINGS
JOB 110706	MANDATORY ELECTRONIC CONTRACT
JOB 110706	MANDATORY ELECTRONIC DOCUMENT SUBMITTAL
JOB 110706	NESTING SITES OF MIGRATORY BIRDS
JOB 110706	PARTNERING REQUIREMENTS
JOB 110706	PERCENT AIR VOIDS AND NDESIGN FOR ACHM SURFACE MIX DESIGNS
JOB 110706	PLASTIC PIPE
JOB 110706	PRESTRESSED CONCRETE MEMBERS
JOB 110706	PRICE ADJUSTMENT FOR ASPHALT BINDER
JOB 110706	PRICE ADJUSTMENT FOR FUEL
JOB 110706	PROHIBITION OF CERTAIN TELECOMMUNICATIONS AND VIDEO SURVEILLANCE SERVICES OR EQUIPMENT
JOB 110706	SECTION 404 NATIONWIDE 23 PERMIT REQUIREMENTS
JOB 110706	SHORING
JOB 110706	SHORING FOR CULVERTS
JOB 110706	SOIL STABILIZATION
JOB 110706	STORM WATER POLLUTION PREVENTION PLAN
JOB 110706	SUBMISSION OF ASPHALT CONCRETE HOT MIX ACCEPTANCE TEST RESULTS
JOB 110706	UTILITY ADJUSTMENTS
JOB 110706	VALUE ENGINEERING
JOB 110706	WARM MIX ASPHALT


GENERAL NOTES

- GRADE LINE DENOTES FINISHED GRADE WHERE SHOWN ON PLANS.
- ALL PIPE LINES, POWER, TELEPHONE, AND TELEGRAPH LINES TO BE MOVED OR LOWERED BY THE RESPECTIVE OWNERS AS PER AGREEMENT WITH SUCH OWNERS.
- ANY EQUIPMENT OR APPURTENANCE THAT INTERFERES WITH THE PROPOSED CONSTRUCTION AND WHICH MAY BE THE PROPERTY OF UTILITY SERVICE ORGANIZATIONS SHALL BE MOVED BY THE OWNERS UNLESS OTHERWISE PROVIDED.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING U. S. MAILBOXES WITHIN THE PROJECT LIMITS IN SUCH A MANNER THAT THE PUBLIC MAY RECEIVE CONTINUED MAIL SERVICE. PAYMENT WILL BE CONSIDERED INCLUDED IN THE PRICE BID FOR THE VARIOUS BID ITEMS.
- ALL LAND MONUMENTS LOCATED WITHIN THE CONSTRUCTION AREA SHALL BE PROTECTED IN ACCORDANCE WITH SECTION 107.12 OF THE STANDARD SPECIFICATIONS.
- ALL TREES THAT DO NOT DIRECTLY INTERFERE WITH THE PROPOSED CONSTRUCTION SHALL BE SPARED AS DIRECTED BY THE ENGINEER. CARE AND DISCRETION SHALL BE USED TO ENSURE THAT ALL TREES NOT TO BE REMOVED SHALL BE HARMED AS LITTLE AS POSSIBLE DURING THE CONSTRUCTION OPERATIONS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING A FENCE TO CONTROL LIVESTOCK IN AREAS WHERE PASTURES ARE SEVERED. WIRE FENCE MAY BE CONSTRUCTED INITIALLY, OR IN LIEU THEREOF, THE CONTRACTOR AT HIS OWN EXPENSE, MAY ELECT TO PROVIDE TEMPORARY FENCING SUITABLE TO CONTAIN LIVESTOCK.
- THE SEQUENCE AS SHOWN ON THE MAINTENANCE OF TRAFFIC PLANS IS A GENERAL OUTLINE FOR THE CONSTRUCTION OF THIS PROJECT, AND IN NO WAY IS IT INTENDED TO COVER EVERY ITEM IN THE PROJECT. ITEMS NOT CRITICAL TO THE CONSTRUCTION SEQUENCE MAY BE CONSTRUCTED IN ANY STAGE AS APPROVED BY THE RESIDENT ENGINEER.
- ALL FLEXIBLE BASE AND ASPHALTIC PAVEMENTS REMOVED SHALL BE PAID FOR UNDER THE ITEM NO. 210 - UNCLASSIFIED EXCAVATION.
- THE EXISTING ASPHALT PAVEMENT TO BE REMOVED FROM THE REMAINING PAVEMENT SHALL BE SEPARATED BY SAWING ALONG A NEAT LINE. AFTER SAWING, THE PAVEMENT TO BE REMOVED SHALL BE CAREFULLY REMOVED IN A MANNER THAT WILL NOT DAMAGE THE PAVEMENT THAT IS TO REMAIN. ANY DAMAGE OF THE ASPHALT PAVEMENT THAT IS TO REMAIN IN PLACE SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE.

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	4	45
TYPICAL SECTIONS OF IMPROVEMENT						



Jun 15 2023 12:12 PM
Docusign



NOTES:


REFER TO CROSS SECTIONS FOR DEVIATION FROM THE NORMAL SLOPES. NO CHANGES SHALL BE MADE FROM THE PLANNED SLOPES WITHOUT THE APPROVAL OF THE ENGINEER.

THE THICKNESS OF AGGREGATE BASE COURSE SHALL BE WITHIN PLUS OR MINUS ONE INCH OF THE PLAN THICKNESS SHOWN. THE CONTRACTOR WILL CORRECT ANY DEFICIENT THICKNESS THAT DOES NOT MEET TOLERANCE INDICATED. PAYMENT WILL NOT BE MADE FOR MATERIAL PLACED IN EXCESS OF THE TOLERANCE INDICATED.

THE FINAL 2" OF SURFACE COURSE IS TO BE PLACED AFTER ALL OTHER COURSES HAVE BEEN LAID. LONGITUDINAL JOINTS SHALL BE AT LANE LINES.

ASPHALT FOR LEVELING OF EXISTING PAVEMENT SHALL BE PLACED ONLY IF AND WHERE DIRECTED BY THE ENGINEER. CALCULATIONS FOR THE AMOUNT OF LEVELING AND LEVELING OPERATIONS SHALL BE PERFORMED BEFORE CONSTRUCTING NOTCH AND WIDENING. CALCULATIONS WILL NOT BE PAID FOR DIRECTLY BUT PAYMENT WILL BE CONSIDERED INCLUDED IN THE VARIOUS PAY ITEMS.


WITH THE APPROVAL OF THE ENGINEER, THE CONTRACTOR WILL BE ALLOWED TO SUBSTITUTE, AT NO ADDITIONAL COST TO THE DEPARTMENT, THE FIRST LIFT OF ACHM SURFACE COURSE (1/2") IN LIEU OF AGGREGATE BASE COURSE ON THE SHOULDERS.




DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	5	45
TYPICAL SECTIONS OF IMPROVEMENT						



Jun 15 2023 12:12 PM
DocuSign



DETOUR - FULL DEPTH SECTION
STA. 202+75.00 TO STA. 204+63.16
STA. 210+45.51 TO STA. 212+46.74



DETOUR - FULL DEPTH SUPERELEVATION SECTION
STA. 204+63.16 TO STA. 210+45.51

NOTES:


REFER TO CROSS SECTIONS FOR DEVIATION FROM THE NORMAL SLOPES. NO CHANGES SHALL BE MADE FROM THE PLANNED SLOPES WITHOUT THE APPROVAL OF THE ENGINEER.

THE THICKNESS OF AGGREGATE BASE COURSE SHALL BE WITHIN PLUS OR MINUS ONE INCH OF THE PLAN THICKNESS SHOWN. THE CONTRACTOR WILL CORRECT ANY DEFICIENT THICKNESS THAT DOES NOT MEET TOLERANCE INDICATED. PAYMENT WILL NOT BE MADE FOR MATERIAL PLACED IN EXCESS OF THE TOLERANCE INDICATED.


DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	6	45
SPECIAL DETAILS						



Jun 15 2023 12:12 PM




DETAIL FOR TRANSITIONS



WIDENING FOR GUARDRAIL

NOTE: REFER TO STD. DWG. GR-9 AND CROSS SECTIONS FOR SLOPE REQUIREMENTS BEHIND GUARDRAIL.




SECTION OF APPROACH SLAB

SEE APPROACH SLAB DETAILS IN BRIDGE DRAWINGS

DATE REVISION	DATE REVISION	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	7	45
SPECIAL DETAILS						




Jun 15 2023 12:12 PM



TYPICAL SECTIONS OF IMPROVEMENT - HWY. 17 DETOUR
STA. 207+30

REFER TO SURVEY CONTROL DETAIL SHEETS FOR HORIZONTAL AND VERTICAL CONTROL DATA.

SPECIAL DETAILS




BM4 3071 5/26/2021 R110706.DGN

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	8	45
TEMPORARY EROSION CONTROL DETAILS						



Jun 15 2023 12:12 PM
DocuSign



STA. 102+75.00
BEGIN JOB 110706
LOG MILE 11.00

STA. 112+35.00
END JOB 110706

LEGEND

- (E-5) = SAND BAG DITCH CHECK
- (E-11) = SILT FENCE

REVISIONS


DATE OF REVISION	REVISION

HWY. 17 - CLEARING & GRUBBING
TEMPORARY EROSION CONTROL DETAILS

DATE REVISION	DATE REVISION	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	9	45



Jun 15 2023 12:12 PM
DocuSign



STA. 102+75.00
BEGIN JOB 110706
LOG MILE 11.00

STA. 112+35.00
END JOB 110706

LEGEND

- (E-5) = SAND BAG DITCH CHECK
- (E-11) = SILT FENCE

REVISIONS


DATE OF REVISION	REVISION

HWY. 17 - STAGE I
TEMPORARY EROSION CONTROL DETAILS

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	10	45
TEMPORARY EROSION CONTROL DETAILS						



Jun 15 2023 12:12 PM
DocuSign



STA. 102+75.00
BEGIN JOB 110706
LOG MILE 11.00

STA. 112+35.00
END JOB 110706

LEGEND

E-5	= SAND BAG DITCH CHECK
E-11	= SILT FENCE

REVISIONS

DATE OF REVISION	REVISION


HWY. 17 - STAGE 2
TEMPORARY EROSION CONTROL DETAILS

BM43071 1/19/2023 R110706.DGN

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	11	45
TEMPORARY EROSION CONTROL DETAILS						



Jun 15 2023 12:13 PM
DocuSign



STA. 102+75.00
BEGIN JOB 110706
LOG MILE 11.00

STA. 112+35.00
END JOB 110706

LEGEND

- (E-5) = SAND BAG DITCH CHECK
- (E-11) = SILT FENCE

REVISIONS

DATE OF REVISION	REVISION


HWY. 17 - STAGE 3
TEMPORARY EROSION CONTROL DETAILS

BM43071 1/19/2023 R110706.DGN

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	12	45
MAINTENANCE OF TRAFFIC DETAILS						



Jun 15 2023 12:13 PM
DocuSign



NOTE: STAGE 2 TRAFFIC IS SHOWN IN THE CROSS SECTIONS

STAGE CONSTRUCTION


CONSTRUCTION STAGING MAINTENANCE OF TRAFFIC DETAILS

BM4 3071 1/19/2023
R110706.DGN




DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	13	45
MAINTENANCE OF TRAFFIC DETAILS						



Jun 15 2023 12:13 PM



ADVANCE WARNING (ALL STAGES)

- 
 (2) W21-5a (36" x 36") ALL STAGES IF AND WHERE DIRECTED BY THE ENGINEER
- 
 (2) R4-1 (24" X 30") ALL STAGES SPACES AT 1/4 MILE INTERVALS
- 
 (2) W8-1 (30" X 30") IF AND WHERE DIRECTED BY THE ENGINEER

ADVANCE WARNING
ALL STAGES
MAINTENANCE OF TRAFFIC DETAILS

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	14	45
MAINTENANCE OF TRAFFIC DETAILS						



Jun 15 2023 12:13 PM
DocuSign

STAGE 1 CONSTRUCTION SEQUENCE:

INSTALL ADVANCE WARNING SIGNS AND END ROAD WORK SIGNS AT THE BEGINNING AND END OF JOB AS SHOWN ON THE ADVANCE WARNING DETAIL.

APPLY LEVELING COURSE TO EXISTING LANES IF AND WHERE DIRECTED BY THE ENGINEER.

CONSTRUCT DETOUR AS SHOWN IN THE STAGE 1 MAINTENANCE OF TRAFFIC DETAILS. INSTALL QUAD. 96' X 73. TEMP. CULVERT AT DETOUR STA. 207+30.

USE TRAFFIC DRUMS SPACED 45' O.C.

STAGE 2 CONSTRUCTION SEQUENCE:

MAINTAIN ADVANCE WARNING SIGNS AT BOTH ENDS OF DETOUR AND END ROAD WORK SIGNS AT THE BEGINNING AND END OF JOB AS SHOWN ON THE ADVANCE WARNING DETAIL.

APPLY CONSTRUCTION PAVEMENT MARKINGS AS SHOWN IN THE STAGE 2 MAINTENANCE OF TRAFFIC DETAILS.

SHIFT TRAFFIC TO NEW DETOUR AS SHOWN IN THE STAGE 2 MAINTENANCE OF TRAFFIC DETAILS.

CONSTRUCT PROPOSED ROADWAY AND BRIDGE. REMOVE AND INSTALL PIPE CULVERT @ STA. 103+65 LT. SIDE.

USE TRAFFIC DRUMS SPACED 20' O.C.

STAGE 3 CONSTRUCTION SEQUENCE:

MAINTAIN ADVANCE WARNING SIGNS AND END ROAD WORK SIGNS AT THE BEGINNING AND END OF JOB AS SHOWN ON THE ADVANCE WARNING DETAIL.


APPLY CONSTRUCTION PAVEMENT MARKINGS AS SHOWN IN THE STAGE 3 MAINTENANCE OF TRAFFIC DETAILS.

SHIFT TRAFFIC TO ROADWAY AS SHOWN IN THE STAGE 3 MAINTENANCE OF TRAFFIC DETAILS.

OBLITERATE DETOUR. CONSTRUCT RIGHT SIDE SLOPES AND DITCHES.

USE TRAFFIC DRUMS SPACED 45' O.C.


APPLY FINAL 2" LIFT ACHM SURFACE COURSE AND PLACE PERMANENT PAVEMENT MARKINGS AS SHOWN IN THE PERMANENT PAVEMENT MARKING DETAILS.



REFER ALSO TO STANDARD DRAWING TC-5 FOR DETAILS OF PLACEMENT OF PCCB TURNBACKS.

NOTE: OM-3L & OM-3R SIGNS SHALL BE EQUALLY SPACED ALONG PCCB TURNBACK.

DETAIL OF OBJECT MARKERS AT PRECAST CONCRETE BARRIER TURNBACKS





DRIVEWAY/TRAFFIC DRUM DETAIL

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	15	45

MAINTENANCE OF TRAFFIC DETAILS



Jun 15 2023 12:13 PM
DocuSign







STAGE I
MAINTENANCE OF TRAFFIC DETAILS

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	16	45

MAINTENANCE OF TRAFFIC DETAILS



Jun 15 2023 12:13 PM
Docusign



STA. 102+75.00
BEGIN JOB 110706
LOG MILE 11.00

STA. 112+35.00
END JOB 110706

STAGE 2
MAINTENANCE OF TRAFFIC DETAILS



DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	17	45

MAINTENANCE OF TRAFFIC DETAILS



Jun 15 2023 12:13 PM
DocuSign

OBLITERATE ROADWAY



STA. 102+75.00
BEGIN JOB 110706
LOG MILE 11.00

STA. 112+35.00
END JOB 110706

ROAD CLOSED (I) R11-2 (48" X 30")

8' BARR. TYP. III RT.
8' BARR. TYP. III RT.

ROAD CLOSED (I) R11-2 (48" X 30")

8' BARR. TYP. III LT.
8' BARR. TYP. III LT.



BM43071 1/19/2023
R110706.DGN

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	18	45
PERMANENT PAVEMENT MARKING DETAILS						



Jun 15 2023 12:14 PM
DocuSign

PERMANENT PAVEMENT MARKINGS
 REFLECTORIZED PAINT PAVEMENT MARKING WHITE (6") = 2320 LIN. FT.
 REFLECTORIZED PAINT PAVEMENT MARKING YELLOW (6") = 2320 LIN. FT.
 RAISED PAVEMENT MARKERS TYPE II (YELLOW/YELLOW) (80' O.C.) = 14 EACH



STA. 102+75.00
 BEGIN JOB 110706
 LOG MILE 11.00

STA. 112+35.00
 END JOB 110706

NOTE: THE 6" YELLOW STRIPING QUANTITY HAS BEEN ESTIMATED BASED ON A DOUBLE YELLOW CENTERLINE STRIPE FOR THE ENTIRE PROJECT. THE PROJECT MUST BE MARKED FOR PASSING/NO PASSING ZONES PRIOR TO THE PLACEMENT OF ANY FINAL STRIPING. CONTACT THE MAINTENANCE DIVISION AFTER THE FINAL LIFT OF SURFACE COURSE HAS BEEN PLACED TO SCHEDULE THE ZONING OF THE PROJECT.

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	19	45
QUANTITIES						



Jun 15 2023 12:14 PM
DocuSign

ADVANCE WARNING SIGNS AND DEVICES

SIGN NUMBER	DESCRIPTION	SIGN SIZE	STAGE 1	STAGE 2	STAGE 3	MAXIMUM NUMBER REQUIRED	TOTAL SIGNS REQUIRED		VERTICAL PANELS	TRAFFIC DRUMS	BARRICADES (TYPE III)		FURNISHING & INSTALLING PRECAST CONC. BARRIER	TEMPORARY IMPACT ATTENUATION BARRIER	TEMP. IMPACT ATTN. BARR. (REPAIR)			
			LIN. FT. - EACH				NO.	SQ. FT.			EACH	RIGHT				LEFT	LIN. FT.	EACH
W20-1	ROAD WORK 1500 FT.	48"x48"	2	2	2	2	2	32.0										
W20-1	ROAD WORK 1000 FT.	48"x48"	2	2	2	2	2	32.0										
W20-1	ROAD WORK 500 FT.	48"x48"	2	2	2	2	2	32.0										
G20-2	END ROAD WORK	48"x24"	2	2	2	2	2	16.0										
R11-2	ROAD CLOSED	48"x30"	2	2	2	2	2	20.0										
OM-3L	OBJECT MARKER	12"x36"		3		3	3	9.0										
OM-3R	OBJECT MARKER	12"x36"		4		4	4	12.0										
W1-6	LARGE ARROW	48"x24"		2		2	2	16.0										
W1-8	CHEVRONS	18"x24"		16		16	16	48.0										
R4-1	DO NOT PASS	24"x30"	2	2	2	2	2	10.0										
W21-5a	RIGHT SHOULDER CLOSED	36"x36"	2	2	2	2	2	18.0										
W8-1	BUMP	30"x30"	2	2	2	2	2	12.5										
	VERTICAL PANELS		22	13	22	22			22									
	TRAFFIC DRUMS		22	19	22	22				22								
	TYPE III BARRICADE-RT. (8')		2	2	2	2					16							
	TYPE III BARRICADE-LT. (8')		2	2	2	2					16							
	FURNISHING AND INSTALLING PRECAST CONCRETE BARRIER			140		140						140						
	TEMPORARY IMPACT ATTENUATION BARRIER			2		2							2					
	TEMPORARY IMPACT ATTENUATION BARRIER (REPAIR)			2		2								2				
TOTALS:								257.5	22	22	16	16	140	2	2			

NOTE: THIS IS A LOW TRAFFIC VOLUME ROAD AS DEFINED IN SECTION 604.03, STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.

CONSTRUCTION PAVEMENT MARKINGS AND PERMANENT PAVEMENT MARKINGS

DESCRIPTION	STAGE 1	STAGE 2	STAGE 3	END OF JOB	CONSTRUCTION PAVEMENT MARKINGS	REMOVABLE CONSTRUCTION PAVEMENT MARKINGS	RAISED PAVEMENT MARKERS		REFLECTORIZED PAINT PAVEMENT MARKING			
	LIN. FT. - EACH						LIN. FT.	LIN. FT.	TYPE II		6"	
									(YELLOW/YELLOW)	WHITE	YELLOW	LIN. FT.
CONSTRUCTION PAVEMENT MARKINGS	4640	3076	4640		12356							
REMOVABLE CONSTRUCTION PAVEMENT MARKINGS		812				812						
RAISED PAVEMENT MARKERS TYPE II (YELLOW/YELLOW)	14	13	14	14			55					
REFLECTORIZED PAINT PAVEMENT MARKING WHITE (6")				2320					2320			
REFLECTORIZED PAINT PAVEMENT MARKING YELLOW (6")				2320						2320		
TOTALS:					12356	812	55	2320	2320			

NOTE: THIS IS A LOW TRAFFIC VOLUME ROAD AS DEFINED IN SECTION 604.03, STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.

NOTE: THE 6" YELLOW STRIPING QUANTITY HAS BEEN ESTIMATED BASED ON A DOUBLE YELLOW CENTERLINE STRIPE FOR THE ENTIRE PROJECT. THE PROJECT MUST BE MARKED FOR PASSING/NO PASSING ZONES PRIOR TO THE PLACEMENT OF ANY FINAL STRIPING. CONTACT THE MAINTENANCE DIVISION AFTER THE FINAL LIFT OF SURFACE COURSE HAS BEEN PLACED TO SCHEDULE THE ZONING OF THE PROJECT.

GUARDRAIL

STATION	STATION	LOCATION	GUARDRAIL (TYPE A)	THRIE BEAM GUARDRAIL TERMINAL	GUARDRAIL TERMINAL (TYPE 2)
			LIN. FT.	EACH	
105+37.75	106+81.50	LT. SIDE	75	1	1
104+62.75	106+81.50	RT. SIDE	150	1	1
108+20.50	110+39.25	LT. SIDE	150	1	1
108+20.50	109+64.25	RT. SIDE	75	1	1
TOTALS:			450	4	4

QUANTITIES

BM4 3071 1/26/2023
R110706.DGN

EROSION CONTROL

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
2/26/24		6	ARK.	110706	20	45
QUANTITIES						



STATION	STATION	LOCATION	PERMANENT EROSION CONTROL					TEMPORARY EROSION CONTROL							
			SEEDING	LIME	MULCH COVER	WATER	SECOND SEEDING APPLICATION	TEMPORARY SEEDING	MULCH COVER	WATER	SAND BAG DITCH CHECKS	ROCK DITCH CHECKS	SILT FENCE	*SEDIMENT REMOVAL & DISPOSAL	
			ACRE	TON	ACRE	M.GAL.	ACRE	ACRE	ACRE	M.GAL.	(E-5) BAG	(E-6) CU.YD.	(E-11) LIN. FT.	CU. YD.	
ENTIRE PROJECT		CLEARING AND GRUBBING													
ENTIRE PROJECT		STAGE 1													
ENTIRE PROJECT		STAGE 2	0.51	1.02	0.51	52.0	0.51		1.32	1.32	26.9	132	126	17	
ENTIRE PROJECT		STAGE 3	1.40	2.80	1.40	142.8	1.40		2.14	2.14	43.7	22		2	
*ENTIRE PROJECT TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER.			0.48	0.96	0.48	49.0	0.48		2.27	2.27	46.3	198	27	599	40
TOTALS:			2.39	4.78	2.39	243.8	2.39		11.33	11.33	231.2	990	27	2995	201

BASIS OF ESTIMATE:
 LIME2 TONS / ACRE OF SEEDING
 WATER.....102.0 M.G. / ACRE OF SEEDING
 WATER.....20.4 M.G. / ACRE OF TEMPORARY SEEDING
 SAND BAG DITCH CHECKS.....22 BAGS / LOCATION
 ROCK DITCH CHECKS.....3 CU.YD./LOCATION

NOTE: THE TEMPORARY EROSION CONTROL DEVICES SHOWN ABOVE AND ON THE PLANS SHALL BE INSTALLED IN SUCH A SEQUENCE AS TO DETER EROSION AND SEDIMENTATION ON U.S. WATERWAYS AS EXPLAINED BY THE NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM PERMIT.

*QUANTITIES ESTIMATED.
 SEE SECTION 104.03 OF THE STD. SPECS.

APPROACH GUTTERS AND SLABS

STATION	STATION	LOCATION	APPROACH GUTTER	APPROACH SLABS	REINFORCING STEEL-RDWY.	AGGREGATE BASE CRS.
			(TYPE SPECIAL)	(TYPE SPECIAL)	(GR. 60)	(CLASS 7)
			CU.YD.	CU.YD.	POUND	TON
106+69.33	106+91.50	HWY. 17 LT.	3.29		471	
106+69.33	106+91.50	HWY. 17 APPROACH SLAB		17.20	1258	14.55
106+69.33	106+91.50	HWY. 17 RT.	3.29		471	
108+10.50	108+32.67	HWY. 17 LT.	3.29		471	
108+10.50	108+32.67	HWY. 17 APPROACH SLAB		17.20	1258	14.55
108+10.50	108+32.67	HWY. 17 RT.	3.29		471	
TOTALS:			13.16	34.40	4400	29.10

NOTE: USE T=13" FOR 4' SHOULDER.

STRUCTURES

STATION	DESCRIPTION	TEMPORARY CULVERTS	STD. DWG. NOS.
		96"	
		LIN. FT.	
207+30	DETOUR - QUAD. 96" X 73' TEMP. CULVERT	292	PCC-1, PCM-1
TOTAL:		292	

NOTE: FOR R.C. PIPE CULVERT INSTALLATIONS USE TYPE 3 BEDDING UNLESS OTHERWISE SPECIFIED.

NOTE: FOR C.M. PIPE CULVERT INSTALLATIONS USE TYPE 2 BEDDING UNLESS OTHERWISE SPECIFIED.

SELECTED PIPE BEDDING

LOCATION	SELECTED PIPE BEDDING
	CU.YD.
	ENTIRE PROJECT TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER
TOTAL:	10

NOTE: QUANTITY ESTIMATED.
 SEE SECTION 104.03 OF THE STD. SPECS.

DRIVEWAYS & TURNOUTS

STATION	SIDE	LOCATION	WIDTH	ACHM SURFACE COURSE (1/2") 220 LBS. PER SQ. YD. (PG 64-22)		AGGREGATE BASE COURSE (CLASS 7)	SIDE DRAINS	STANDARD DRAWINGS
				FEET	SQ. YD.			
				TON	TON			
103+65	LT	HWY. 17	24	104.56	11.50	42.70	42	DR-2, PCC-1, PCM-1, PCP-1, PCP-2, PCP-3
* ENTIRE PROJECT TEMPORARY DRIVES						50.00		
TOTALS:				104.56	11.50	92.70	42	

BASIS OF ESTIMATE:
 ACHM SURFACE COURSE (1/2").....94.2% MIN. AGGR.....5.8% ASPHALT BINDER

* QUANTITY ESTIMATED
 SEE SECTION 104.03 OF THE STD. SPECS.
 TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER.

NOTE: FOR R.C. PIPE CULVERT INSTALLATIONS USE TYPE 3 BEDDING UNLESS OTHERWISE SPECIFIED.
 NOTE: FOR C.M. PIPE CULVERT INSTALLATIONS USE TYPE 2 BEDDING UNLESS OTHERWISE SPECIFIED.

REMOVAL AND DISPOSAL OF CULVERTS

STATION	DESCRIPTION	PIPE CULVERTS
		EACH
		103+65
TOTAL:		1

NOTE: QUANTITIES SHOWN ABOVE SHALL INCLUDE REMOVAL & DISPOSAL OF ALL HEADWALLS AND FLARED END SECTIONS IF APPLICABLE.

CLEARING AND GRUBBING

STATION	STATION	LOCATION	CLEARING	GRUBBING
			STATION	
			101+00	111+00
TOTALS:			11	11


DATE REVISED	DATE REVISED	FED. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	22	45
07603 - QUANTITIES - 65977						

SCHEDULE OF BRIDGE QUANTITIES - JOB NO. 110706

BRIDGE NO.	NAME PLATE TITLE	UNIT OF STRUCTURE	ITEM NO.	205	801	SP, SS, & 802	SP, SS, & 802	SP, SS, & 802	SP & 803	SS & 804	SS & 804	SS & 805	SS & 805	SS & 805	812	SS & 816	SS & 816	
			ITEM	REMOVAL OF EXISTING BRIDGE STRUCTURE (SITE NO. _)	UNCLASSIFIED EXCAVATION FOR STRUCTURES - BRIDGE	CLASS S CONCRETE - BRIDGE	CLASS S(AE) CONCRETE - BRIDGE	PRESTRESSED CONCRETE BEAMS (NON-VOIDED 15" x 47 3/4")	CLASS 2 PROTECTIVE SURFACE TREATMENT	REINFORCING STEEL - BRIDGE (GRADE 60)	EPOXY COATED REINFORCING STEEL (GRADE 60)	① STEEL SHELL PILING (18" DIA.)	① STEEL SHELL PILING (24" DIA.)	PILE ENCASEMENT	BRIDGE NAME PLATE (TYPE D)	DUMPED RIPRAP	FILTER BLANKET	
			UNIT	LUMP SUM	CU. YD.	CU. YD.	CU. YD.	LIN. FT.	SQ. YD.	LB.	LB.	LIN. FT.	LIN. FT.	LIN. FT.	EACH	CU. YD.	SQ. YD.	
07603	HIGHWAY 17 OVER BOAT GUNWALE SLASH	BENT 1		23	15.32					2,020	420	240				49	83	
		BENT 2			15.43					2,100	580		270	55				
		BENT 3			15.43					2,100	580		270	55				
		BENT 4		23	15.32					2,020	420	240						
		119'-0" PRECAST PRESTRESSED BEAM UNIT				102.90	936.0	494.0		23,180					1	59	101	
		SITE NO. 1 (EXIST. BRIDGE NO. M0465)	1															
TOTALS FOR BRIDGE NO. 07603				46	61.5	102.90	936.0	494.0	8,240	25,180	480	540	110	1	108	184		

THOMAS GERARD
DESIGN SECTION SUPERVISOR

① Steel Shell Piles shall conform to ASTM A252, Grade 3, Fy=45ksi.



SCHEDULE OF BRIDGE QUANTITIES
BOAT GUNWALE SLASH STR. & APPRS. (S)
MONROE COUNTY

ROUTE 17 SEC. 1
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.

DRAWN BY: CGP DATE: 01/17/2023 FILENAME: b110706_q1.dgn
 CHECKED BY: JJ DATE: 01/18/2023 SCALE: NO SCALE
 DESIGNED BY: - DATE: -
 BRIDGE NO. 07603 DRAWING NO. 65977

SUMMARY OF QUANTITIES

ITEM NUMBER	ITEM	QUANTITY	UNIT
201	CLEARING	11	STATION
201	GRUBBING	11	STATION
202	REMOVAL AND DISPOSAL OF PIPE CULVERTS	1	EACH
SP, SS, & 210	UNCLASSIFIED EXCAVATION	10705	CU. YD.
SP & 210	COMPACTED EMBANKMENT	8922	CU. YD.
SP & 210	SOIL STABILIZATION	100	TON
SP, SS, & 303	AGGREGATE BASE COURSE (CLASS 7)	2154	TON
SS & 401	TACK COAT	813	GAL.
SP, SS, & 406	MINERAL AGGREGATE IN ACHM BINDER COURSE (1")	101	TON
SP, SS, & 406	ASPHALT BINDER (PG 64-22) IN ACHM BINDER COURSE (1")	5	TON
SP, SS, & 407	MINERAL AGGREGATE IN ACHM SURFACE COURSE (1/2")	1344	TON
SP, SS, & 407	ASPHALT BINDER (PG 64-22) IN ACHM SURFACE COURSE (1/2")	83	TON
SP & 412	COLD MILLING ASPHALT PAVEMENT	444	SQ. YD.
SP, SS, & 414	ASPHALT CONCRETE PATCHING FOR MAINTENANCE OF TRAFFIC	5	TON
SP, SS, & 415	ACHM PATCHING OF EXISTING ROADWAY	5	TON
SP, SS, & 504	APPROACH SLABS	34.40	CU. YD.
SP, SS, & 504	APPROACH GUTTERS	13.16	CU. YD.
601	MOBILIZATION	1.00	LUMP SUM
SP & 602	FURNISHING FIELD OFFICE	1	EACH
SS & 603	MAINTENANCE OF TRAFFIC	1.00	LUMP SUM
603	96" TEMPORARY CULVERT	292	LIN. FT.
SS & 604	SIGNS	258	SQ. FT.
SS & 604	BARRICADES	32	LIN. FT.
SS & 604	TRAFFIC DRUMS	22	EACH
SS & 604	FURNISHING AND INSTALLING PRECAST CONCRETE BARRIER	140	LIN. FT.
604	CONSTRUCTION PAVEMENT MARKINGS	12356	LIN. FT.
SS & 604	REMOVABLE CONSTRUCTION PAVEMENT MARKINGS	812	LIN. FT.
SS & 604	VERTICAL PANELS	22	EACH
SP, SS, & 606	18" SIDE DRAIN	42	LIN. FT.
SS & 606	SELECTED PIPE BEDDING	10	CU. YD.
SS & 611	4" PIPE UNDERDRAINS	500	LIN. FT.
SS & 611	UNDERDRAIN OUTLET PROTECTORS	2	EACH
SS & 617	GUARDRAIL (TYPE A)	450	LIN. FT.
SS & 617	GUARDRAIL TERMINAL (TYPE 2)	4	EACH
SS & 617	THREE BEAM GUARDRAIL TERMINAL	4	EACH
620	LIME	5	TON
620	SEEDING	2.39	ACRE
SS & 620	MULCH COVER	13.72	ACRE
620	WATER	475.0	M. GAL.
621	TEMPORARY SEEDING	11.33	ACRE
621	SILT FENCE	2995	LIN. FT.
621	SAND BAG DITCH CHECKS	990	BAG
621	SEDIMENT REMOVAL AND DISPOSAL	201	CU. YD.
621	ROCK DITCH CHECKS	27	CU. YD.
623	SECOND SEEDING APPLICATION	2.39	ACRE
635	ROADWAY CONSTRUCTION CONTROL	1.00	LUMP SUM
718	REFLECTORIZED PAINT PAVEMENT MARKING WHITE (6")	2320	LIN. FT.
718	REFLECTORIZED PAINT PAVEMENT MARKING YELLOW (6")	2320	LIN. FT.
721	RAISED PAVEMENT MARKERS (TYPE II)	55	EACH
SS & 731	TEMPORARY IMPACT ATTENUATION BARRIER	2	EACH
SS & 731	TEMPORARY IMPACT ATTENUATION BARRIER (REPAIR)	2	EACH
SS & 804	REINFORCING STEEL-ROADWAY (GRADE 60)	4400	POUND
STRUCTURES OVER 20' SPAN			
205	REMOVAL OF EXISTING BRIDGE STRUCTURE (SITE NO. 1)	1.00	LUMP SUM
636	BRIDGE CONSTRUCTION CONTROL	1.00	LUMP SUM
801	UNCLASSIFIED EXCAVATION FOR STRUCTURES-BRIDGE	46	CU. YD.
SP, SS, & 802	CLASS S CONCRETE-BRIDGE	62	CU. YD.
SP, SS, & 802	CLASS S(AE) CONCRETE-BRIDGE	103	CU. YD.
SP, SS, & 802	PRESTRESS CONCRETE BEAMS (NON-VOIDED 15" X 47 3/4")	936	LIN. FT.
SP & 803	CLASS 2 PROTECTIVE SURFACE TREATMENT	494	SQ. YD.
SS & 804	REINFORCING STEEL-BRIDGE (GRADE 60)	8240	POUND
SS & 804	EPOXY COATED REINFORCING STEEL (GRADE 60)	25180	POUND
SS & 805	STEEL SHELL PILING (18" DIAMETER)	480	LIN. FT.
SS & 805	STEEL SHELL PILING (24" DIAMETER)	540	LIN. FT.
SS & 805	PILE ENCASEMENT	110	LIN. FT.
812	BRIDGE NAME PLATE (TYPE D)	1	EACH
SS & 816	FILTER BLANKET	184	SQ. YD.
SS & 816	DUMPED RIPRAP	108	CU. YD.

REVISIONS

DATE	REVISION	SHEET NUMBER
2/26/2024	REVISED DISTRICT MAP ON TITLE SHEET TO MOVE LOGAN COUNTY TO DISTRICT 8. ADDED SUPPLEMENTAL SPECIFICATIONS "CONTACT INFORMATION FOR MOTORIST DAMAGE CLAIMS", "ASPHALT LABORATORY FACILITY", "RECYCLED ASPHALT PAVEMENT", AND "GUARDRAIL DELINEATORS". ADDED SPECIAL PROVISION "PERCENT AIR Voids AND NDESIGN FOR ACHM SURFACE MIX DESIGNS". REMOVED SPECIAL PROVISION "TOTAL SOLAR ECLIPSE". REVISED QUANTITIES "COMPACTED EMBANKMENT", "MINERAL AGGREGATE IN ACHM BINDER COURSE (1")", "ASPHALT BINDER (PG-22) IN ACHM BINDER COURSE (1")", "MINERAL AGGREGATE IN ACHM SURFACE COURSE (1/2")", AND "ASPHALT BINDER (PG 64-22) IN ACHM SURFACE COURSE (1/2)". REVISED SPECIAL PROVISIONS "PRICE ADJUSTMENT FOR ASPHALT BINDER" AND "PRICE ADJUSTMENT FOR FUEL". REVISED F.A.P. NUMBER. ADDED SUPPLEMENTAL SPECIFICATION "PREQUALIFICATION OF BIDDERS". REMOVED SPECIAL PROVISIONS "ESTABLISHING CONTRACT TIME - WORKING DAY CONTRACT" & "FLEXIBLE BEGINNING OF WORK". ADDED SPECIAL PROVISION "FLEXIBLE BEGINNING OF WORK - CALENDAR DAY CONTRACT". REVISED TIME TAB IN PRECONSTRUCTION.	1,3,20,21,23
7/24/2024	REMOVED SUPPLEMENTAL SPECIFICATIONS "CEMENT", "CEMENT", AND "CEMENT". ADDED SUPPLEMENTAL SPECIFICATIONS "CEMENT TREATED BASE COURSE", "CEMENT STABILIZED CRUSHED STONE BASE COURSE", "PORTLAND CEMENT CONCRETE PAVEMENT", AND "CONCRETE FOR STRUCTURES." REVISED SPECIAL PROVISION "UTILITY ADJUSTMENTS".	3, 23
9/4/2024		3, 23


SUMMARY OF QUANTITIES & REVISIONS

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
2/26/24		6	ARK.	110706	23	45
7/24/24		SUMMARY OF QUANTITIES & REVISIONS				
9/4/24						



09-05-2024

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	24	45
SURVEY CONTROL DETAILS						



Jun 15 2023 12:14 PM
DocuSign

SURVEY CONTROL COORDINATES

Project Name: s110706
 Date: 7/17/2020
 Coordinate System: ARKANSAS STATE PLANE - NORTH ZONE BASED ON GPS CONTROL, STATIC POINTS 1 & 2 PROJECTED TO GROUND.
 Units: U.S. SURVEY FOOT

Point Name	Northing	Easting	Elev	Feature	Description
1	1995759.2226	1561026.1768	168.743	GPS	ARDOT STD. MON. STAMPED PN: 1
2	1997308.7053	1561034.0770	169.455	GPS	ARDOT STD. MON. STAMPED PN: 2
3	1998063.1769	1561007.7966	168.441	CTL	ARDOT STD. MON. STAMPED PN: 3
4	1998512.3215	1561010.1659	168.943	CTL	ARDOT STD. MON. STAMPED PN: 4
5	1999124.9808	1561057.1267	168.186	CTL	ARDOT STD. MON. STAMPED PN: 5
6	1999686.0962	1561069.8126	168.902	CTL	ARDOT STD. MON. STAMPED PN: 6
900	1998407.1807	1561013.0190	170.350	TBM	CHSLD SQUARE IN SW COR BR

HWY. 17

POINT NO.	TYPE	STATION	NORTHING	EASTING
8000	PI	102+44.03	1997950.2888	1561023.6689
8001	PC	104+67.32	1998173.5768	1561024.9300
8003	PT	106+30.65	1998336.8954	1561027.0165
8004	POE	118+37.03	1999543.0320	1561051.0237

*Note - Rebar and Cap - Standard - 5/8" Rebar with 2" Aluminum Cap stamped
 *(standard markings common to all caps), or as indicated
 (other markings indicated in the point description of the individual point).
 ALL DISTANCES ARE GROUND.
 USE CAF = 1.0 FOR STAKEOUT FOR THIS PROJECT.
 A PROJECT CAF OF 0.999954700214 HAS BEEN USED TO COMPUTE THE ABOVE GROUND COORDINATES.
 THIS CAF IS INTENDED FOR USE WITHIN THE PROJECT LIMITS.
 GRID DISTANCE = GROUND DISTANCE X CAF.
 GRID COORDINATES ARE STORED UNDER FILE NAME s110706gi.CTL
 HORIZONTAL DATUM: NAD 83 (2011)
 VERTICAL DATUM: NAVD 88 POSITIONAL ACCURACY THIRD ORDER, UNLESS SPECIFIED OTHERWISE
 AT A SPECIFIC POINT.

HWY. 17 DETOUR

POINT NO.	TYPE	STATION	NORTHING	EASTING
8100	PC	202+75.00	1997981.2601	1561023.8438
8102	PT	204+22.31	1998126.6780	1561044.4301
8103	PC	205+04.01	1998205.2853	1561066.6614
8105	PT	206+43.54	1998342.9262	1561087.1484
8106	PC	208+67.41	1998566.7454	1561091.6034
8108	PT	210+02.39	1998700.6637	1561077.6543
8109	PC	211+11.75	1998807.2043	1561052.9922
8111	PT	212+46.74	1998941.1226	1561039.0432


REFERENCE POINTS (1500 SERIES) ARE TO BE USED TO ESTABLISH CONTROL
 IF THE PRIMARY CONTROL POINTS LISTED ABOVE HAVE BEEN DESTROYED.
 REFERENCE POINTS ARE NOT TO BE USED FOR VERTICAL CONTROL

BASIS OF BEARING:
 ARKANSAS STATE PLANE GRID BEARINGS - 0301-NORTH ZONE
 DETERMINED FROM GPS CONTROL POINTS: STATIC POINTS 1 & 2
 CONVERGENCE ANGLE: 00°27'43.51" RIGHT AT PN: 4 LT: N34°32'58.00" LG: W91°10'27.81"
 GRID AZIMUTH = ASTRONOMICAL AZIMUTH - CONVERGENCE ANGLE.

DATE REVISION	DATE REVISION	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	25	45
SURVEY CONTROL DETAILS						



Jun 15 2023 12:14 PM



HWY. 17 DETOUR
 P.I. = 205+74.16
 Δ = 14°39'05" LT.
 D = 10°30'00"
 T = 70.15'
 L = 139.53'
 P.C. = 205+04.01
 P.T. = 206+43.54
 e = 0.100'/'
 Ls = 300'

HWY. 17 DETOUR
 P.I. = 209+35.25
 Δ = 14°10'25" LT.
 D = 10°30'00"
 T = 67.84'
 L = 134.98'
 P.C. = 208+67.41
 P.T. = 210+02.39
 e = 0.100'/'
 Ls = 300'

HWY. 17
 P.I. = 105+48.99
 Δ = 0°49'00" RT.
 D = 0°30'00"
 T = 81.67'
 L = 163.33'
 P.C. = 104+67.32
 P.T. = 106+30.65
 NO SUPER

HWY. 17 DETOUR
 P.I. = 203+49.11
 Δ = 15°28'05" RT.
 D = 10°30'00"
 T = 74.11'
 L = 147.31'
 P.C. = 202+75.00
 P.T. = 204+22.31
 NO SUPER


HWY. 17 DETOUR
 P.I. = 211+79.59
 Δ = 14°10'25" RT.
 D = 10°30'00"
 T = 67.84'
 L = 134.99'
 P.C. = 211+11.75
 P.T. = 212+46.74
 NO SUPER

DETOUR STA. 202+75.00 =
 HWY. 17 STA. 102+75.00
 BEGIN DETOUR

DETOUR STA. 212+46.74 =
 HWY. 17 STA. 112+35.00
 END DETOUR

STA. 102+75.00
 BEGIN JOB 110706
 LOG MILE 11.00


STA. 112+35.00
 END JOB 110706



DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	26	45
SURVEY CONTROL DETAILS						



Jun 15 2023 12:15 PM
 DocuSign



HWY. 17
 SURVEY CONTROL DETAILS

STA.	STA.	SIDE	GUARDRAIL (TYPE A) LIN. FT.	GUARDRAIL TERMINAL (TYPE 2) EACH	THREE BEAM GUARDRAIL TERMINAL EACH
104+62.75	106+81.50	RT.	150		
105+37.75	106+81.50	LT.	75		
108+20.50	109+64.25	RT.	75		
108+20.50	110+39.25	LT.	150		


STA. 107+00.00 - STA. 107+95.14 IN PLACE
 95.0' X 25.0' R.C. CHANNEL BEAM
 BR. NO. M0465
 REMOVE AS EXISTING BRIDGE STRUCTURE
 (SITE NO. 1) = 1.00 LUMP SUM

STA. 106+91.50 BRIDGE END
 BRIDGE NO. 07603
 119'-0" PRECAST CONCRETE BEAM UNIT
 (39.5'-40'-39.5')
 30'-0" CLEAR ROADWAY
 119'-0" TOTAL LENGTH
 STA. 108+10.50 BRIDGE END
 025 = 1620 CFS
 & D.A. = 35.7 SQ. MI.


STA. 103+65 IN PLACE
 18" X 26' C.M. PIPE CULVERT
 LT. SIDE DRAIN
 REMOVE AND INSTALL
 18" X 42' PIPE CULVERT
 LT. SIDE DRAIN
 CONSTRUCT APPROACH = 70 CU. YDS.

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	27	45


PLAN AND PROFILE SHEETS



Jun 15 2023 12:15 PM



REFER TO SURVEY CONTROL DETAIL SHEETS FOR HORIZONTAL AND VERTICAL CONTROL DATA.



STA. 102+75.00
 BEGIN JOB 110706
 LOG MILE 11.00

STA. 112+35.00
 END JOB 110706

NOTE: FOR ALL THE CONSTRUCTION OF TEMPORARY RAMPS OR HAUL ROADS, THIS STREAM IS CLASSIFIED AS A PERENNIAL STREAM. THE STREAM BANK ELEVATION IS 160 FT. MSL. BETWEEN STATIONS 207+18 AND 207+84. REFER TO SECTION 110.05 (c) OF THE 2014 STANDARD SPECIFICATIONS.

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	28	45

PLAN AND PROFILE SHEETS




Jun 15 2023 12:15 PM

STA. 207+30 INSTALL
QUAD. 96" X 73" TEMP. PIPE CULVERT
ON 15° LT. FWD. SKEW
96" TEMPORARY PIPE CULVERT = 292 LIN. FT.


HWY. 17 DETOUR
P.I. = 205+74.16
Δ = 14°39'05" LT.
D = 10°30'00"
T = 70.15'
L = 139.53'
P.C. = 205+04.01
P.T. = 206+43.54
e = 0.100'/'
Ls = 300'

HWY. 17 DETOUR
P.I. = 209+35.25
Δ = 14°10'25" LT.
D = 10°30'00"
T = 67.84'
L = 134.98'
P.C. = 208+67.41
P.T. = 210+02.39
e = 0.100'/'
Ls = 300'

HWY. 17 DETOUR
P.I. = 211+79.59
Δ = 14°10'25" RT.
D = 10°30'00"
T = 67.84'
L = 134.99'
P.C. = 211+11.75
P.T. = 212+46.74
NO SUPER



REFER TO SURVEY CONTROL DETAIL SHEETS FOR HORIZONTAL AND VERTICAL CONTROL DATA.




DETOUR STA. 202+75.00 =
HWY. 17 STA. 102+75.00
BEGIN DETOUR

STA. 204+63.16 BEGIN SUPERELEVATION (N.C.)
STA. 205+73.77 MAX SUPERELEVATION (0.036'/'')
STA. 209+34.90 MAX SUPERELEVATION (0.036'/'')
STA. 210+45.51 END SUPERELEVATION (N.C.)

DETOUR STA. 212+46.74 =
HWY. 17 STA. 112+35.00
END DETOUR




DATE REVISED	DATE REVISED	FIG. NO. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	29	45
07603 - LAYOUT - 65978						



HYDRAULIC DATA

FLOOD DESCRIPTION	FREQUENCY	DISCHARGE	NATURAL WATER SURFACE ELEVATION	WATER SURFACE ELEV. WITH BACKWATER
	YEARS	CFS	FEET	FEET
Design	25	1620	162.8	163.2
Base	100	1950	163.2	163.5
Extreme	500	2330	163.5	164.0
Overtopping	>500	-	-	-

① Unconstricted water surface elevation without structure or roadway approaches.
 Q100 backwater elevation for existing structure = 163.2 ft
 Proposed Low Bridge Chord elevation = 168.5
 Drainage Area = 35.7 square miles
 Historical H.W. Elev. = 171.7




SHEET 1 OF 2
 LAYOUT OF BRIDGE
 HIGHWAY 17 OVER BOAT GUNWALE SLASH
 BOAT GUNWALE SLASH STR. & APPRS. (S)
 MONROE COUNTY

ROUTE 17 SEC. 1
 ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: RD DATE: 07/26/2021 FILENAME: b110706_L1.dgn
 CHECKED BY: MCB DATE: 08/24/2021 SCALE: 1" = 10'-0"
 DESIGNED BY: JWP DATE: 05/24/2021
 BRIDGE NO. 07603 DRAWING NO. 65978

PRINT DATE: 3/13/2023

DATE REVISED	DATE REVISED	FIG. NO. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	30	45
07603 - LAYOUT - 65979						



GENERAL NOTES

BENCHMARK: Vertical Control Data are shown on the Survey Control Data Sheets.

CONSTRUCTION SPECIFICATIONS: Arkansas State Highway and Transportation Department Standard Specifications for Highway Construction (2014 edition) with applicable Supplemental Specifications and Special Provisions. Section and Subsection refer to the Standard Construction Specifications unless otherwise noted in the Plans.

DESIGN SPECIFICATIONS: AASHTO LRFD Bridge Design Specifications, Eighth Edition (2017).

LIVE LOADING: HL-93

SEISMIC ZONE: 2 SD1: 0.27 SITE CLASS: D

SEISMIC OPERATIONAL CLASSIFICATION: Other

MATERIALS AND STRENGTHS:

Class S(AE) Concrete (Superstructure)	f'c = 4,000 psi
Class S Concrete (Substructure)	f'c = 3,500 psi
Class S Concrete (Prestressed Beams)	f'c = 5,000 psi
Reinforcing Steel (AASHTO M 31 or M 322, Type A)	fy = 60,000 psi
Prestressing Strands (AASHTO M203, Gr. 270)	fpu = 270,000 psi
Structural Steel (ASTM A709, Gr. 36)	Fy = 36,000 psi
Structural Steel (ASTM A709, Gr. 50 or Gr. 50W)	Fy = 50,000 psi

BORING LOGS: Boring logs may be obtained from the Construction Contract Development Section of the Program Management Division.

STEEL SHELL PILING: Piling in Bents 1 and 4 shall be 18" diameter concrete filled steel shell piles and shall be driven to a minimum ultimate bearing capacity of 147 tons per pile. Piling in Bents 2 and 3 shall be 24" diameter concrete filled steel shell piles and shall be driven to a minimum ultimate bearing capacity of 279 tons per pile. All piling shall be driven with an approved air, steam, or diesel hammer to a minimum tip elevation of 112.50 or lower at Bents 1 and 4 and to a minimum tip elevation of 119.00 or lower at Bents 2 and 3. Piling in end bents shall be driven after embankment to bottom of cap is in place. Lengths of piling shown are assumed for estimating quantities only. Actual lengths are to be determined in the field. No additional payment will be made for cut-off or build-up. Test piles are not required but may be driven for the Contractor's information in accordance with Subsection 805.08(g). No piles will be paid for as test piles.

DRIVING SYSTEM: The driving system approval and the ultimate bearing capacity determination for piling shall be based on the requirements of Subsection 805.09(b), "Method B Wave Equation Analysis (WEAP)". It is estimated that the minimum rated hammer energy required to obtain the ultimate bearing capacity for all piles will be 42,000 foot pounds per blow.

PILE ENCASEMENT: Pile encasement for Bents 2 and 3 shall extend from bottom of cap to 3' below natural or finished ground. See Std. Dwg No. 55021 for additional information.

BRIDGE DECK: The concrete bridge deck shall be given a tined finish as specified for the final finishing in Subsection 802.19 for Class 5 Tined Bridge Roadway Surface Finish.

PROTECTIVE SURFACE TREATMENT: Class 2 Protective Surface Treatment shall be applied to the roadway surface and to the roadway face and top of the concrete bridge rails in accordance with Section 803.

DETAIL DRAWINGS:

End Bents	DRAWING NO. 65980 - 65981
Intermediate Bents	65982
119'-0" Precast Prestressed Concrete Beam Unit	65983-65986
Concrete Filled Steel Shell Piling	55021
Bridge Traffic Rail Type SSTR36	55070
Type Special Approach Slabs	65987
Type Special Approach Gutters	65988

EXISTING BRIDGE: Existing Bridge No. M0465 (Log Mile 11.08) is 25.0' wide (23.7' clear roadway) and 95.0' long and consists of 5 - 19'-0" precast concrete spans supported by timber piles. The existing bridge is located along centerline of the proposed new bridge. Plans of the existing structure, if available, may be obtained upon request to the Construction Contract Development Section of the Program Management Division.

REMOVAL AND SALVAGE: After the Detour is open to traffic, the Contractor shall remove existing Bridge No. M0465 in accordance with Section 205. Existing remnant timber piling from a previous structure shall also be removed to a depth of 2' below subgrade or final ground surface. This work will not be paid for directly but shall be considered subsidiary to the item "Removal of Existing Bridge Structure (Site No.)". All material from the existing bridge shall become the property of the Contractor except the following which shall remain the property of the State:

Guardrail Beams and Posts

MAINTENANCE OF TRAFFIC: See Roadway Plans.


BORING LEGEND

- A1-Moist, Soft, Brown Silty Clay with Sand
- B1-Moist, Brown Silty Clay with Sand (Manganese Nodules)
- C1-Wet, Gray Silt with Some Organic Matter (Wood)
- D1-Wet, Medium Stiff, Gray Lean Clay
- E1-Moist, Gray Lean Clay with Sand
- F1-Wet, Medium Dense, Gray Poorly Graded Sand with Silt
- G1-Wet, Medium Dense, Gray Sand with Clay
- H1-Wet, Medium Dense, Gray Poorly Graded Sand
- J1-Wet, Medium Dense, Gray Poorly Graded Sand with Some Gravel
- K1-Wet, Medium Dense, Gray Poorly Graded Sand with Trace Gravel
- L1-Sand with Gravel
- M1-Wet, Medium Dense, Gray Poorly Graded Sand with Trace Gravel and Trace Organic Matter (Wood)
- N1-Wet, Dense, Gray Poorly Graded Sand with Silt
- P1-Moist, Medium Stiff, Brown Sandy Clay
- Q1-Moist, Very Loose, Brown Sandy Silt
- R1-Moist, Gray Silt with Sand
- S1-Moist, Stiff, Brown Sandy Clay
- T1-Moist, Gray Sandy Lean Clay (Manganese Nodules)
- U1-Wet, Loose, Gray Sand with Silt
- V1-Wet, Loose, Gray Sand with Some Organic Matter (Wood)
- W1-Wet, Medium Dense, Gray Sand with Silt
- X1-Wet, Medium Dense, Gray Sand with Trace Gravel
- Y1-Wet, Dense, Gray Sand with Trace Gravel
- Z1-Wet, Medium Dense, Gray Sand

- A2-Wet, Medium Dense, Gray Sand with Some Gravel
- B2-Wet, Medium Dense, Gray Clayey Sand with Trace Gravel
- C2-Wet, Dense, Gray Sand and Trace Gravel
- D2-Wet, Medium Dense, Gray Clayey Sand
- E2-Wet, Medium Dense, Gray Sand with Silt and Some Gravel
- F2-Wet, Dense, Brown Sand with Gravel
- G2-Moist, Medium Dense, Gray Silt

"N" VALUES

Sta. 106+60 - 11' Left of C.L. Bridge & C.L. Construction			
3.0 - 4.0, N=3	55.5 - 56.5, N=25		
4.7 - 5.7, N=3	60.5 - 61.5, N=16		
11.7 - 12.7, N=5	65.5 - 66.5, N=24		
20.5 - 21.5, N=25	70.5 - 71.5, N=21		
25.5 - 26.5, N=16	75.5 - 76.5, N=18		
30.5 - 31.5, N=16	80.5 - 81.5, N=26		
35.5 - 36.5, N=25	85.5 - 86.5, N=27		
40.5 - 41.5, N=22	90.5 - 91.5, N=25		
45.5 - 46.5, N=25	95.5 - 96.5, N=29		
50.5 - 51.5, N=24	100.5 - 101.5, N=38		
Sta. 108+35 - 18' Right of C.L. Bridge & C.L. Construction			
3.0 - 4.0, N=5	60.5 - 61.5, N=21		
4.8 - 5.8, N=5	65.5 - 66.5, N=11		
7.3 - 8.3, N=4	70.5 - 71.5, N=19		
11.3 - 12.3, N=10	75.5 - 76.5, N=18		
20.5 - 21.5, N=14	80.5 - 81.5, N=35		
25.5 - 26.5, N=9	85.5 - 86.5, N=15		
30.5 - 31.5, N=7	90.5 - 91.5, N=19		
35.5 - 36.5, N=12	95.5 - 96.5, N=25		
40.5 - 41.5, N=14	100.5 - 101.5, N=29		
45.5 - 46.5, N=23	105.5 - 106.5, N=32		
50.5 - 51.5, N=45	110.5 - 111.5, N=48		
55.5 - 56.5, N=21	115.5 - 116.5, N=30		



SHEET 2 OF 2
LAYOUT OF BRIDGE
HIGHWAY 17 OVER BOAT GUNWALE SLASH
BOAT GUNWALE SLASH STR. & APPRS. (S)
MONROE COUNTY

ROUTE 17 SEC. 1
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.


DRAWN BY: RD DATE: 07/26/2021 FILENAME: b110706_L1.dgn
 CHECKED BY: MCB DATE: 08/24/2021 SCALE: 1" = 10'-0"
 DESIGNED BY: JWP DATE: 05/24/2021
 BRIDGE NO. 07603 DRAWING NO. 65979

PRINT DATE: 3/13/2023

DATE REVISED	DATE REVISED	FIG. NO. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	31	45
07603 - END BENTS - 65980						


- Riser stirrup bars to be spaced and lapped 1'-0" min. with cap stirrup bars as shown.
- Dowel bars B1101E shall be drilled and grouted into the cap with an approved epoxy. Embedment shown is approximate. Actual embedment and hole size shall be in accordance with the epoxy manufacturer's recommendations. Dowel bars B1101E to project thru bearing pads 18" into preformed holes in prestressed beams. Preformed holes in prestressed beams to be filled with an approved non-shrink grout. Adjust cap reinforcing as necessary to miss B1101E bars.

NOTE:
See Dwg. No. 65981 for "VIEW E-E".




PLAN

1/2" = 1'-0"




ELEVATION

LOOKING BACK
1/2" = 1'-0"




SECTION A-A

1" = 1'-0"




SECTION B-B

1" = 1'-0"



SECTION C-C

1" = 1'-0"







SHEET 1 OF 2
DETAILS OF END BENTS

ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.


DRAWN BY: CGP DATE: 12/21/2022 FILENAME: b110706_b1.dgn
CHECKED BY: JJ DATE: 12/29/2022 SCALE: AS NOTED
DESIGNED BY: JJ DATE: 12/2022
BRIDGE NO. 07603 DRAWING NO. 65980

DATE REVISED	DATE REVISED	FIG. NO. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	32	45
07603 - END BENTS - 65981						



BAR LIST - PER BENT




MARK	NO. REQ'D	LENGTH	P.D.	BENDING DIAGRAMS
B401	6	34'-3"	Str.	
B402	8	2'-8"	Str.	
B403	16	4'-11"	Str.	
B404	6	12'-6"	Str.	
B405	19	5'-6"	2"	
B501	34	11'-2"	2 1/2"	
B502	15	7'-10"	2 1/2"	
B601	6	35'-7"	4 1/2"	
B602	6	34'-3"	Str.	
B1101E	32	2'-6"	Str.	
W401	44	4'-6"	Str.	Dimensions are out to out of bars. Bars with an "E" suffix are to be epoxy coated.
W601	24	10'-2"	Str.	
W602	8	4'-1"	4 1/2"	




SHEET 2 OF 2
DETAILS OF END BENTS
 ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.
 DRAWN BY: CGP DATE: 12/21/2022 FILENAME: b110706_b1.dgn
 CHECKED BY: JJ DATE: 12/29/2022 SCALE: AS NOTED
 DESIGNED BY: JJ DATE: 12/2022
 BRIDGE NO. 07603 DRAWING NO. 65981

DATE REVISED	DATE REVISED	FIG. NO. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	33	45
07603 - INTERMEDIATE BENTS - 65982						

- Riser stirrup bars to be spaced and lapped with cap stirrup bars as shown.
- Dowel bars B1101E shall be drilled and grouted into the cap with an approved epoxy. Embedment shown is approximate. Actual embedment and hole size shall be in accordance with the epoxy manufacturer's recommendations. Dowel bars B1101E to project thru bearing pads 18" into preformed holes in prestressed beams. Preformed holes in prestressed beams to be filled with an approved non-shrink grout. Adjust cap reinforcing as necessary to miss B1101E bars.





Bent	Elev. "A"	Elev. "B"
2	168.84	165.01
3	168.81	164.98



BAR LIST - PER BENT

MARK	NO. REQ'D	LENGTH	P.D.	BENDING DIAGRAMS
B401	6	32'-2"	Str.	
B402	8	1'-5"	Str.	
B403	16	4'-5"	Str.	
B404E	33	6'-10"	2"	
B405	22	6'-0"	2"	
B406	6	10'-8"	Str.	
B501	48	13'-2"	2 1/2"	
B502	20	9'-3"	2 1/2"	
B701	6	33'-10"	5 1/4"	
B801	6	32'-2"	Str.	
B1101E	32	2'-6"	Str.	

NOTE:
B405 bars to be spaced and tied to B501 or B502 bars as shown.



DETAILS OF INTERMEDIATE BENTS
ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.
DRAWN BY: CGP DATE: 12/29/2022 FILENAME: b110706_b2.dgn
CHECKED BY: JJ DATE: 01/06/2023 SCALE: AS NOTED
DESIGNED BY: JJ DATE: 12/2022
BRIDGE NO. 07603 DRAWING NO. 65982

PRINT DATE: 4/14/2023



Dimensions are out to out of bars.
Bars with an "E" suffix are to be epoxy coated.

DATE REVISED	DATE REVISED	FIG. NO. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	34	45
07603 - SPAN DETAILS - 65983						


NOTE:
Bar positions and clearances from the forms shall be maintained by means of stays, ties, hangers, or other approved devices sufficient in size and number to prevent displacement during construction, per Subsection 804.06.

Slab Reinforcing
 Longitudinal: S502E in top (place as shown)
 2-S601E in top (place as shown), see "REINFORCING PLAN & DECK POURING SEQUENCE", Dwg. No. 65986.
 Transverse: S501E @ 12" o.c. in top
 S503E @ 12" in top of overhangs (bundled with #5 bars) both sides


NOTE:
Class 2 Protective Surface Treatment shall be applied to the roadway face and top of the concrete bridge rail and to the roadway surface.
 ① "X" is 6½" at C.L. Bearing based on theoretical beam camber, dead load deflections of cast-in-place concrete slab, and a constant grade. The Contractor shall adjust these values for the vertical curve along the bridge unit.
 ② See "ROUNDING DETAIL".




TYPICAL ROADWAY SECTION




END BENT SECTION
1" = 1'-0"



INTERMEDIATE BENT SECTION
1" = 1'-0"



NOTE:
Backer Rods and Preformed Joint filler shall not be paid for directly, but shall be considered subsidiary to the item "Prestressed Concrete Beams (Non-Voided 15" x 47¾")."




SHEET 1 OF 4
DETAILS OF PRECAST
PRESTRESSED BEAM UNIT

ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: CGP DATE: 11/01/2022 FILENAME: b110706_s1.dgn
 CHECKED BY: JJ DATE: 12/08/2022 SCALE: AS NOTED
 DESIGNED BY: JJ DATE: 10/2022
 BRIDGE NO. 07603 DRAWING NO. 65983

PRINT DATE: 4/14/2023

DATE REVISED	DATE REVISED	FIG. NO. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	35	45
07603 - SPAN DETAILS - 65984						



FRAMING PLAN

GENERAL NOTES

PRESTRESSED BEAMS:

Prestensioning steel shall be 0.6" diameter Low Relaxation strands with a minimum ultimate strength of 270 ksi and shall conform to AASHTO M 203.

Prestressing strands and steel reinforcing bars in the beam will not be paid for directly, but will be subsidiary to the item "Prestressed Concrete Beam (Non-Voided 15" x 47 3/4)".

All beams shall be non-voided 15" x 47 3/4" rectangular beams as shown on the details. Chamfer all exposed corners to 3/8".

All work and materials shall be as specified in Subsection 802.22.

Concrete shall be Class "S" and shall have a minimum 28 day compressive strength $f'_c = 5,000$ psi. The initial tensile force applied to each 0.6" diameter strand shall be 44,000 pounds except as noted. Transfer of this tensioning load to the beam shall not be done until the compressive strength of the concrete is 4,000 psi.

Dimensions shown are to the center of strands.

The Contractor shall submit the method and sequence for release of strands to the Engineer for approval prior to casting of the beams.

Beam length shown on the design plans are net lengths measured horizontally along beam centerlines. The beam fabricator shall make the necessary allowances for grade and shortening, creep and shrinkage.

Exposed steel at beginning and end of bridge shall be protected against corrosion after cutting strands by a coating of two layers of zinc-rich paint.

After detensioning, saw cut, grind, or bend up strands as designated by the plans. Heat-cutting or bending methods shall not be used within 6" of the beams.

Extreme care shall be exercised in handling and moving Precast Prestressed Concrete Beams. Beams must be maintained in an upright position at all times and must be picked up from points near the girder ends. Disregard of this requirement may lead to the collapse of the beam. The Contractor's proposed lifting details shall be submitted on shop drawings to the Engineer for approval. The use of holes for lifting purposes will not be permitted.

The points of support and direction of reactions with respect to the member shall be approximately the same during transport and storage as when member is in its final position.

The Contractor may submit alternate strand patterns with design calculations for review and approval in accordance with Subsection 802.22 except that only 0.6" diameter strands shall be allowed.

Distances from the forms and spacing of the Prestressed Steel shall be maintained by stays, ties, hangers, spacers or other approved supports which shall be on the Shop Drawings.

Drawings show general features of design only. Shop drawings shall be submitted to the Engineer and approval shall be secured before fabrication can begin.

SUPERSTRUCTURE NOTES:


CONCRETE:

All concrete, except for prestressed beams, shall be Class S(AE) with a minimum 28 day compressive strength $f'_c = 4,000$ psi. Concrete shall be poured in the dry and all exposed corners shall be chamfered 3/4" unless otherwise noted.

The concrete deck (roadway surface) shall be given a tined finish in accordance with Subsection 802.19 for Class 5 Tined Bridge Roadway Surface Finish. Movement of the finishing machine across new concrete shall be on planks placed on the surface and shall be prohibited for 72 hours after finishing the pour. Sufficient concrete must be placed ahead of the strike-off to fully load the beam. When permitted, the use of a longitudinal strike-off will require that a vertical camber adjustment be made in the strike-off to account for the future dead load deflection due to any railings.

REINFORCING STEEL:

All reinforcing steel shall be Grade 60 conforming to AASHTO M 31 or M 322, Type A, with mill test reports and shall be epoxy coated. The reinforcing steel is to be accurately located in the forms and firmly held in place by steel wire supports, sufficient in number and size to prevent displacement during the course of construction. The wire supports will not be paid for directly, but will be considered subsidiary to the item "Epoxy Coated Reinforcing Steel (Grade 60)".








**SHEET 2 OF 4
DETAILS OF PRECAST
PRESTRESSED BEAM UNIT**

ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.

DRAWN BY: CGP DATE: 11/01/2022 FILENAME: b110706_s1.dgn
CHECKED BY: JJ DATE: 12/08/2022 SCALE: 3/16" = 1'-0"
DESIGNED BY: JJ DATE: 10/2022
BRIDGE NO. 07603 DRAWING NO. 65984

PRINT DATE: 4/14/2023

DATE REVISED	DATE REVISED	FIG. NO. DWT. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	36	45
07603 - SPAN DETAILS - 65985						



BAR LIST - ALL BEAMS

MARK	NO. REQ'D	LENGTH	P.D.
D401	4512	6'-3 1/2"	2"
D402	1872	2'-10 1/2"	2"
D403	576	4'-6 1/2"	2"
D404	96	7'-5 1/2"	2"
D405	96	4'-8 1/2"	2"
D601	120	38'-8"	Str.
P403E	488	5'-6"	①






Table is symmetrical about the C.L. Unit

"X" is Dead Load Deflection of Slab + Composite Dead Load
 "Y" is expected Camber of Beam at 90 days after release (Prestress + Dead Load of Beam).

CAMBER & DEFLECTIONS (INCHES)




NOTE:
 "X" & "Y" are based on the required minimum strength and may vary from the dimensions shown. "X" & "Y" shall be measured along bottom of beams unless otherwise approved by the Engineer. See Slab Tolerance on Dwg. No. 65986 for limitations of the beams final position under dead load. The Contractor is responsible for any adjustment necessary to meet slab thickness tolerance and to achieve an acceptable finished grade. No payment shall be made for any additional concrete in the slab when camber is less than shown.

SPECIAL CAMBER NOTES

The camber and dead load deflection values shown on the plans are estimated based on the required minimum concrete strength for the precast prestressed concrete beam units. The contractor shall provide the Engineer with the following information:

- Actual 28-day concrete strength of prestressed concrete beams.
- Estimated age of prestressed concrete beams at time of erection which shall not be less than 90 days from release.
- Profile of each beam under its own weight.
- Number of days since release of strands of each beam.

Following receipt of the above data, the Engineer will provide an updated camber and deflection diagram to the Contractor, if necessary.



SHEET 3 OF 4
DETAILS OF PRECAST PRESTRESSED BEAM UNIT


ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: CGP DATE: 11/01/2022 FILENAME: b110706_s1.dgn
 CHECKED BY: JJ DATE: 12/08/2022 SCALE: AS NOTED
 DESIGNED BY: JJ DATE: 10/2022
 BRIDGE NO. 07603 DRAWING NO. 65985

PRINT DATE: 4/14/2023

Dimensions are out to out of bars.
 Bars with an "E" suffix are to be epoxy coated.

DATE REVISED	DATE REVISED	FED. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	37	45
07603 - SPAN DETAILS - 65986						



- ① Placed as shown in "TYPICAL ROADWAY SECTION", Dwg. No. 65983. Lap splice locations of adjacent bars shall be staggered to prevent bars from being spliced at the same location.
- ⓕ C.L. Full Depth Rail Joint (formed width 1/4" to 1" max.) Stop 6" from top of deck/slab.
- ⓐ C.L. Partial Depth Rail Joint (formed width 1/4" to 1" max.) Stop 1'-4" from top of deck/slab.


REINFORCING PLAN & DECK POURING SEQUENCE

NOTES:

The topping slab shall not be poured less than 90 days following the release of the prestressing strands. Pours with the same number may be placed simultaneously or separately. All Pours 1 must be placed before Pours 2 can be placed. A minimum of 48 hours shall elapse between the end of a pour and the start of the next pour. A minimum of 72 hours shall elapse between the end of a pour and the start of an adjacent pour. Concrete Diaphragms at bents 2 & 3 shall be poured monolithically with the deck. A minimum of 72 hours shall elapse between the completion of the bridge deck pour and the start of the railing pour. Any railing pours made before the entire slab unit has been placed must be approved by the Engineer. The Contractor must obtain approval from the Engineer for any deviations from the pouring sequence shown.

Concrete in bridge superstructure shall be placed, consolidated, and screeded off for the entire pour before any concrete has taken its initial set. This may require the use of a retarding agent.

Required slab joints and pouring sequence construction joints shall align with bridge rail joints.



Use Type 3 or 4 Joint Sealer. See Subsections 501.02(h) and 501.05(j). Backer Rod filler will not be required. Joint Sealer shall be measured and paid for as Class S(AE) Concrete-Bridge. Slab Joints shall extend to the outside edge of the deck slab and shall align with open joints at the front face of the bridge rail. Slab joints shall be installed before the bridge railing is poured. If slab joints are to be sawed, they shall be sawed as soon as the concrete has sufficiently set to allow sawing of the joint without damage to the slab. Slab joints shall be placed at all pouring sequence construction joints and required slab joint locations. The joint sealer shall extend across the deck from gutterline to gutterline.

TRANSVERSE SLAB JOINT DETAIL

TABLE OF VARIABLES

Closed Rail Panels			Open Rail Panels					
Panel Length	A	R4XXE	Panel Length	B	C	D	E	R4XXE
9'-6"	18	R404E	20'-0"	14	5'-0"	11	6'-0"	R406E
10'-0"	19	R405E						


NOTES:

See "REINFORCING PLAN & DECK POURING SEQUENCE" for rail panel lengths.
 See "BAR LIST" for rebar quantities.
 See "TABLE OF VARIABLES" for all rebar information.
 See Std. Dwg. No. 55070 for details of rail reinforcing, and location of bars with an "R" prefix.


BAR LIST

MARK	NO. REQ'D	LENGTH	P.D.
P403E	See Dwg. No. 65985		
R400E	48	5'-3"	2 1/2"
R401E	556	6'-4"	2 1/2"
R402E	96	5'-6"	Str.
R404E	32	9'-2"	Str.
R405E	64	9'-8"	Str.
R406E	48	19'-8"	Str.
S401E	8	32'-2"	Str.
S501E	121	32'-2"	Str.
S502E	96	40'-5"	Str.
S503E	238	3'-3"	Str.
S601E	66	39'-1"	Str.
S602E	66	35'-9"	Str.

Bars with an "E" suffix are to be epoxy coated.



REBAR DETAIL
NO SCALE



BRIDGE ENGINEER






**SHEET 4 OF 4
DETAILS OF PRECAST
PRESTRESSED BEAM UNIT**

ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: CGP DATE: 11/01/2022 FILENAME: b110706_s1.dgn
 CHECKED BY: JJ DATE: 12/08/2022 SCALE: AS NOTED
 DESIGNED BY: JJ DATE: 10/2022
 BRIDGE NO. 07603 DRAWING NO. 65986

PRINT DATE: 4/14/2023

DATE REVISED	DATE REVISED	FED. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	38	45
07603 - TYPE SPECIAL APPROACH SLAB - 65987						



GENERAL NOTES

All concrete shall be Class S (AE) with a minimum 28 day compressive strength $f'_c = 4,000$ psi and shall be poured in the dry.

All reinforcing steel shall be Grade 60 (yield strength = 60,000 psi) conforming to AASHTO M 31 or M 322, Type A, with mill test reports.

Approach Slabs will be measured and paid for in accordance with Section 504.

BAR LIST FOR ONE APPROACH SLAB

	Mark	No. Req'd.	Length
22'-0" Slab Width	S401	18	21'-8"
	S402	28	3'-0"
	S403	22	2'-8"
	S501	44	19'-8"

TABLE OF QUANTITIES FOR ONE APPROACH SLAB (FOR INFORMATION ONLY)

Slab Width	Reinforcing Steel (lbs.)	Concrete (cu. yds.)
22'-0"	1258	17.20



DETAILS FOR TYPE SPECIAL APPROACH SLAB
 ROUTE SEC.
 ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: CGP DATE: 02/13/2023 FILENAME: b110706_as.dgn
 CHECKED BY: JJ DATE: 02/14/2023 SCALE: AS SHOWN
 DESIGNED BY: JJ DATE: 02/2023
 BRIDGE NO. 07603 DRAWING NO. 65987

DATE REVISED	DATE REVISED	FIG. NO. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	39	45
07603 - TYPE SPECIAL APPROACH GUTTER - 65988						


GENERAL NOTES

Concrete shall be Class S(AE) (f'c = 4,000 psi).

Reinforcing Steel shall conform to AASHTO M 31 or M 322, Type A with Mill Test Reports Gr. 60 (fy = 60,000 psi).

Approach Gutters will be measured and paid for in accordance with Section 504 of the Standard Specifications.


Surface finish for Approach Gutters to match that used on the bridge deck.



PLAN OF APPROACH GUTTERS


3/8" = 1'-0"

NOTE:
See Std. Dwg. No. 55070 for rail details.



LONGITUDINAL SECTION THRU GUTTER


3/8" = 1'-0"



SECTION A-A


3/4" = 1'-0"

① Match Roadway slope as required at a given approach gutter location.



SECTION B-B

3/4" = 1'-0"



SECTION C-C

NO SCALE

BAR LIST FOR ONE TYPE SPECIAL APPROACH GUTTER


MARK	NO. REQ'D	LENGTH	P.D.
G401	1	9'-8"	Str.
G402	9	10'-10"	Str.
G403	7	4'-11"	Str.
G404	7	4'-5"	Str.
G501	1	9'-8"	Str.
G502	9	19'-8"	Str.
G601	20	4'-11"	Str.
G602	2	4'-5"	Str.
R401E	20	6'-4"	②
R402E	4	5'-6"	Str.
R403E	20	3'-6"	②
R404E	8	9'-8"	Str.

Bars with an "E" suffix are to be epoxy coated.

② See Bending Diagram on Std. Dwg. No. 55070

QUANTITIES FOR ONE TYPE SPECIAL APPROACH GUTTER





Length (ft.)	Reinforcing Steel (lbs.)	Concrete (cubic yards)
20'-0"	471	3.29







DETAILS FOR TYPE SPECIAL APPROACH GUTTER
 ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: CGP DATE: 01/05/2023 FILENAME: b110706_ag.dgn
 CHECKED BY: JJ DATE: 01/12/2023 SCALE: AS NOTED
 DESIGNED BY: JJ DATE: 01/2023
 BRIDGE NO. 07603 DRAWING NO. 65988

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	40	45
CROSS SECTIONS						





CROSS SECTION STA. 101+75 TO STA. 103+00






CROSS SECTION STA. 103+65 TO STA. 106+00

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	42	45
CROSS SECTIONS						






DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	43	45
CROSS SECTIONS						



5/11/2023
BM43071
R110706.DGN





DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	44	45
CROSS SECTIONS						



CROSS SECTION STA. 109+00 TO STA. 111+00


BM43071 7/1/2021
 R110706.DGN

DATE REVISED	DATE REVISED	FED. RD. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
		6	ARK.	110706	45	45
CROSS SECTIONS						




CROSS SECTION STA. 112+00 TO STA. 113+35


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
							JOB NO.	
							1	EMBANKMENT & BACKFILL 55000




EMBANKMENT CONSTRUCTION AND FOOTING BACKFILL AT VERTICAL WALL ABUTMENTS




EMBANKMENT CONSTRUCTION AT SPILL-THROUGH PILE END BENTS




EMBANKMENT CONSTRUCTION AND FOOTING BACKFILL AT SPILL-THROUGH END BENTS




VERTICAL WALL ABUTMENTS



SPILL-THROUGH END BENTS WITH STUB WING



SPILL-THROUGH END BENTS WITH TURNBACK WING



SPILL-THROUGH END BENTS WITH TRANSITION WING

METHOD OF DETERMINING FILL SLOPE LOCATION AT BRIDGE ENDS

GENERAL NOTES

The Bridge End Embankment shall be defined as a section of embankment, not less than 20 feet long adjacent to the bridge end, together with the side slopes and slopes under the bridge end including around the end of wingwalls. Embankment adjacent to structures shall be constructed in 6 inch horizontal layers (loose measure) and compacted by the use of mechanical equipment to the satisfaction of the Engineer. Refer to Subsections 210.09, 210.10 and 801.08 for construction requirements.

STANDARD DETAILS FOR EMBANKMENT CONSTRUCTION AND BACKFILL AT BRIDGE ENDS

ARKANSAS STATE HIGHWAY COMMISSION

LITTLE ROCK, ARK.



DRAWN BY: KDH DATE: 2-27-2014 FILENAME: b55000.dgn
 CHECKED BY: BEF DATE: 2-27-2014 SCALE: NO SCALE
 DESIGNED BY: STD. DATE: -

DRAWING NO. 55000

DATE REVISED	DATE REVISED	FED. DIST. NO.	STATE	JOB NO.	SHEET NO.	TOTAL SHEETS
4-14-23		6	ARK.			
TYPE D NAME PLATE - 55010						

The name of the bridge as shown on the plans shall be placed on Lines 1 & 2 using 1/8" raised letters and numerals 3/8" high.

Line 1	Example 1 RED RIVER	Example 2 SOUTHERN RAILROAD OVERPASS	Example 3 SALINE RIVER RELIEF	Example 4 HIGHWAY 5
Line 2	RELIEF			



GENERAL NOTES

Specifications: Arkansas State Highway and Transportation Department Standard Specifications for Highway Construction, (2014 Edition) with applicable Supplemental Specifications and Special Provisions.

Name plates shall be cast bronze and shall meet the material requirements as specified in Section 812.

Body of plate shall be 1/4" thick and shall include four tapering cone lugs 3/8" to 1/6" x 2" long. The border and all lettering shall be raised 1/8" above the face of plate and shall be polished.

All lettering shall be plain gothic, square cut and not tapered.

The number of plates required and the location and name on the plate for each bridge shall be as designated on the plans.

1 Revised and Redrawn
4-14-23 CGP Checked By: CRE

STANDARD DETAILS FOR TYPE D BRIDGE NAME PLATE

ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.

DRAWN BY: KDH DATE: 2-27-2014 FILENAME: b55010.dgn
CHECKED BY: BEF DATE: 2-27-2014 SCALE: NO SCALE
DESIGNED BY: STD. DATE:

DRAWING NO. 55010

TYPICAL BRIDGE NAME PLATE


Place the Bridge number here using 1/8" raised letters and numerals 1/4" high. Examples: A1234 05432

Place the name of the company awarded the construction contract here using 1/8" raised letters and numerals 3/8" high. Example: ABCD CONSTRUCTION, INC.

Place the Year in which Contract was awarded here using 1/8" raised numerals 3/8" high. Example: 2001


Place the design live loading here using 1/8" raised letters and numerals 1/4" high. Examples: HS20 HL-93

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
3/24/16				6	ARK.			
JOB NO.							STEEL SHELL PILES	55021




CONCRETE FILLED STEEL SHELL PILE

- ① Pile anchorage shall be placed to minimize interference with anchor bolts and reinforcing in cap or footing.
- ② Welding shall comply with ANSI/AWS D1.4 Structural Welding Code-Reinforcing Steel and applicable portions of ANSI/AWS D1.5 Bridge Welding Code.



GENERAL NOTES FOR CONCRETE FILLED STEEL SHELL PILES:

Steel shells shall conform ASTM A252, Grade 3 (Fy = 45,000 psi).
 Concrete used for filling of steel shell shall be Class S with a minimum 28-day compressive strength, f'c = 3,500 psi, and shall be poured in the dry.
 Steel shell piling that extends above the ground and is not protected by pile encasement shall be painted in accordance with Subsection 805.02.
 See Bridge Layout for size and estimated length of steel shell piles and for driving information.
 Concrete, structural steel, reinforcing steel (including welding), and painting shall not be paid for directly, but shall be considered subsidiary to the item "Steel Shell Piling".



ALTERNATE PILE ANCHORAGE DETAIL

Note: Hooked bars shall be oriented to provide the required concrete clearances shown in the plans.







TABLE OF VARIABLES

OUTSIDE DIAMETER "D"	NOMINAL SHELL THICKNESS "T"	PLATE THICKNESS "X"	PLATE THICKNESS "Y"	NO. OF HOOKED BARS FOR ALTERNATE PILE ANCHORAGE	MINIMUM CONICAL TIP DESIGN LOAD (KIPS)
14"	0.50"	2 1/4"	1 1/2"	5	859
16"	0.50"	2 1/4"	1 1/2"	5	986
18"	0.50"	2 1/2"	1 1/2"	6	1,114
20"	0.50"	2 1/2"	1 3/4"	6	1,241
24"	0.50"	2 3/4"	1 3/4"	8	1,495

ALTERNATE FLAT TIP DETAIL
 Note: The alternate flat tip detail shall not be used on steel shell piling to be driven through embankments constructed with internal geosynthetic reinforcement.




ALTERNATE VANED TIP DETAIL




GENERAL NOTES FOR PILE ENCASEMENTS:

See Bridge Layout for additional notes, any pile encasement restrictions and required location of pile encasements.
 Concrete shall be Class S with a minimum 28-day compressive strength, f'c = 3,500 psi. If concrete cannot be placed in the dry, Seal Concrete may be used from top to bottom of encasement.
 Reinforcing steel shall be Grade 60 conforming to AASHTO M 31 or M 322, Type A.
 Welded wire fabric shall conform to AASHTO M 55 or M 221.
 Concrete, welded wire fabric or reinforcing steel, and galvanized pipe shall not be paid for directly, but shall be considered subsidiary to the item "Pile Encasement".




PILE ENCASEMENT DETAIL FOR STEEL SHELL PILES

- ③ Unless otherwise noted on Bridge Layout.
- ④ See Bridge Layout for height of pile encasement (3'-0" Minimum).
- ⑤ Pile encasement, when not extended to bottom of cap, shall have 2" concrete taper for water runoff as shown in the detail for partial height encasement.



ALTERNATE PILE ENCASEMENT DETAIL FOR STEEL SHELL PILES

This document was originally issued and sealed by Charles R. Ellis, PE No. 9235, on March 24, 2016. This copy is not a signed and sealed document.



STANDARD DETAILS FOR CONCRETE FILLED STEEL SHELL PILES AND PILE ENCASEMENTS



ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.
 DRAWN BY: A.M.S. DATE: 2/27/2014 FILENAME: b55021.dgn
 CHECKED BY: B.E.F. DATE: 2/27/2014 SCALE: NO SCALE
 DESIGNED BY: STD. DATE: —
 BRIDGE ENGINEER
 DRAWING NO. 55021

Revised and added various details by KWy, Ck'd. by BEF, 3/24/16.


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
							JOB NO.	
							TYPE E APPROACH SLAB	55040E

Notes:
The surface finish for Approach Slabs shall match that used on the bridge deck.
All longitudinal lines within the limits of horizontal curves shall be on curves concentric to C.L. Bridge. Adjustment to longitudinal bar lengths may be required. Transverse reinforcing shall be placed on radial lines to C.L. Bridge.

BENDING DIAGRAMS



PLAN - SKEWED APPROACH SLAB WITH APPROACH GUTTERS



PLAN - SQUARE APPROACH SLAB


BAR LIST

(Square & Skewed Approach Slabs)

Slab Width	Square		Skewed		
	Mark	No. Req'd.	Length	No. Req'd.	Length
20'-0"	S401	18	19'-8"	22	19'-8"
	S402	—	—	20	9'-10"
	S403	28	3'-0"	*	3'-0"
	S404	20	7'-2"	20	7'-2"
	S4...	—	—	1 Ea.	19.7' - 1.25'/(tan skew angle) to 2'-0" Min.
22'-0"	S401	18	21'-8"	22	21'-8"
	S402	—	—	22	9'-10"
	S403	28	3'-0"	*	3'-0"
	S404	22	7'-2"	22	7'-2"
	S4...	—	—	1 Ea.	21.7' - 1.25'/(tan skew angle) to 2'-0" Min.
24'-0"	S401	18	23'-8"	22	23'-8"
	S402	—	—	24	9'-10"
	S403	28	3'-0"	*	3'-0"
	S404	24	7'-2"	24	7'-2"
	S4...	—	—	1 Ea.	23.7' - 1.25'/(tan skew angle) to 2'-0" Min.
24'-0"	S501	48	19'-8"	—	—
	S501 - S548	—	—	1 Ea.	19.6' + 0.25' (tan skew angle) to 19.6' + 23.75' (tan skew angle)
	S401	18	35'-8"	22	35'-8"
	S402	—	—	36	9'-10"
	S403	28	3'-0"	*	3'-0"
36'-0"	S404	36	7'-2"	36	7'-2"
	S4...	—	—	1 Ea.	35.7' - 1.25'/(tan skew angle) to 2'-0" Min.
	S501	72	19'-8"	—	—
	S501 - S572	—	—	1 Ea.	19.6' + 0.25' (tan skew angle) to 19.6' + 35.75' (tan skew angle)


*Varies with skew angle

1/2" x 1" Poured Jt. Sealer (Type 3 or 4) per Subsection 501.02(h)(2) Backer rod is not required.




DETAILS OF LONGITUDINAL CONSTRUCTION JOINT

1/2" x 1" Poured Jt. Sealer (Type 3 or 4) per Subsection 501.02(h)(2) Backer rod is not required.




SECTION A-A

N.T.S.




SECTION B-B

AT ASPHALT APPROACH PAVEMENT N.T.S.



SECTION B-B

AT CONCRETE APPROACH PAVEMENT N.T.S.



SECTION X-X

SQUARE APPROACH SLAB SHOWN 1/4" = 1'-0"

SECTION Y-Y

N.T.S.

GENERAL NOTES

This drawing is for use with Reinforced Concrete Slab Spans in Seismic Performance Zones 2, 3 & 4 and for the maximum skew angles shown below:

- 20'-0" Slab Width: Maximum Skew Angle = 45°
- 22'-0" Slab Width: Maximum Skew Angle = 45°
- 24'-0" Slab Width: Maximum Skew Angle = 40°
- 36'-0" Slab Width: Maximum Skew Angle = 30°

All concrete shall be Class S (AE) with a minimum 28 day compressive strength f'c = 4,000 psi and shall be poured in the dry.

All reinforcing steel shall be Grade 60 (yield strength = 60,000 psi) conforming to AASHTO M 31 or M 322, Type A, with mill test reports.

Approach Slabs will be measured and paid for in accordance with Section 504.

TABLE OF QUANTITIES FOR ONE SQUARE APPROACH SLAB

(FOR INFORMATION ONLY)

Slab Width	Reinforcing Steel (Lbs.)	Concrete (Cu. Yds.)
20'-0"	1210	15.60
22'-0"	1325	17.20
24'-0"	1440	18.70
36'-0"	2135	28.10

STANDARD DETAILS FOR TYPE E APPROACH SLAB


ARKANSAS STATE HIGHWAY COMMISSION

LITTLE ROCK, ARK.

DRAWN BY: A.M.S. DATE: 2/27/2014 FILENAME: b55040e.dgn
 CHECKED BY: K.W.Y. DATE: 2/27/2014 SCALE: AS SHOWN
 DESIGNED BY: STD. DATE:



DRAWING NO. 55040E

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
09/27/2022				6	ARK.			
				JOB NO.				




- TYPE SSTR36 - 55070
- C.L. Full-Depth Rail Joint (formed width 1/2" to 1" max). Stop 6" from top of deck/slab or sidewalk. Place at all intermediate bents locations where rail is continuous.
- All measurements shown are along gutterline at base of rail.
 - Minimum embedment into deck/slab.
 - Eliminate recess when formliner with architectural finish is used. See Plans for additional information.
 - C.L. 1" ϕ formed holes for 7/8" ϕ bolts. See Standard Drawings GR-10 and GR-12 for additional information.
 - Only applicable for bridges with rail cast directly on bridge deck/slab surface. Increase height as necessary for sidewalks, see Plans for additional information.
 - Field bend front leg of R401E bar as required to maintain minimum 1 1/2" front face clearance within limits of taper.
 - When optional slip forming is used: to control cracking, all rail joints must be V-grooved around the perimeter of the rail prior to concrete set and sawing. Depth of V-groove shall be 1/2". Sawing of the joints shall be done as soon as practical to a width of 1/4", and must be controlled so it will follow the V-Groove.
 - End posts shall be the same length within a panel.

ELEVATION - SINGLE SLOPE TRAFFIC RAIL



Bolt Special End Shoe to face of rail as shown. Tapered washers are not required between the head of the bolts and the sloped face of the rail. Tighten the five terminal connection bolts in a well distributed pattern to prevent damage or distortion of the three-beam connection. Cut bolts off after installation so as to extend no more than 3/4" beyond nut. Paint ends of cut-off bolts with zinc-rich paint. This work and material will not be paid for directly but shall be considered subsidiary to associated contract items.



- Required Construction Joint. Level where water flows away from rail, match roadway slope where water flows toward rail.
- Top of Abutment Wing & Required Construction Joint (match bridge deck/slab construction joint slope). See Plans for Wing reinforcing.
- These bars will not be included in the "Table of Variables". See Plans for details.

TABLE OF VARIABLES

Panel Length	Closed Rail Panels			Open Rail Panels				
	A	R4XXE	Panel Length	B	C	D	E	R4XXE
See Plans for table with values.								

GENERAL NOTES

This rail has been successfully evaluated by full-scale crash test to meet MASH TL-4 criteria.


Details shown are general for bridges without sidewalks. See Plans for additional details and requirements specific to bridges with sidewalks.

For Table of Variables, Rail Bar List, locations of Full and Partial Depth Rail Joints, and Wing & Rail Bar Lists, see Plans.

For location of drain openings, see Plans. Drain openings shown are not applicable for bridges with sidewalks. Drain openings will not be allowed over Railroad Right of Way, travelled roadways, and protected waterways.

Rail Terminus details, including Rail Taper, are not applicable for bridges with sidewalks or when bridge railing is continuous with roadway railing.

Scales shown are for 22"x34" drawings. When using 11"x17" drawings, reduce scale by one half.



DETAILS OF OPTIONAL SLIP FORMING OF BRIDGE TRAFFIC RAIL

Modified bending diagram and spacing for R401E bar. No Scale

By: CGP, Checked by: CMW 09/27/2022

This document was originally issued and sealed by Charles R. Ellis, PE No. 9235, on November 5, 2020. This copy is not a signed and sealed document.

THESE DETAILS ARE APPLICABLE UNLESS OTHERWISE SHOWN IN THE PLAN DETAILS, SPECIAL PROVISIONS, OR SUPPLEMENTAL SPECIFICATIONS.


STANDARD DETAILS FOR BRIDGE TRAFFIC RAIL TYPE SSTR36

ARKANSAS STATE HIGHWAY COMMISSION

LITTLE ROCK, ARK.


DRAWN BY: KKY DATE: 11/5/2020 FILENAME: b55070.dgn
 CHECKED BY: LJB DATE: 11/5/2020 SCALE: As Noted
 DESIGNED BY: STD. DATE: -----

DRAWING NO. 55070




NOTE:
REFER TO PLAN SHEETS
FOR WIDTH OF COUNTY ROAD.


NOTE: TURNOUTS SHALL BE MODIFIED
WHERE NECESSARY TO MEET LOCAL
CONDITIONS AS DIRECTED BY THE ENGINEER.

 ACHM SURFACE COURSE (1/2")
(220 LBS. PER SQ. YD.) AND
AGGREGATE BASE COURSE (CLASS 7)
7" COMP. DEPTH, UNLESS OTHERWISE
SPECIFIED IN PLANS.


DETAIL FOR COUNTY ROAD TURNOUTS
OPEN SHOULDER SECTION



NOTE: TURNOUTS AND PRIVATE DRIVES
SHALL BE MODIFIED WHERE NECESSARY
TO MEET LOCAL CONDITIONS AS DIRECTED
BY THE ENGINEER.


 ACHM SURFACE COURSE (1/2")
(220 LBS. PER SQ. YD.) AND
AGGREGATE BASE COURSE (CLASS 7)
7" COMP. DEPTH IF ASPHALT OR
GRAVEL DRIVE EXISTING; OR 6"
CONCRETE IF CONCRETE DRIVE
EXISTING.

DETAIL FOR DRIVEWAY TURNOUTS
OPEN SHOULDER SECTION
(ARTERIALS)





NOTE:
PAVEMENT STRUCTURE FOR STATE HIGHWAYS, CITY STREETS,
& COUNTY ROADS TO BE SAME AS MAIN LANES.

DETAIL OF TURNOUTS, ASPHALT STREETS,
COUNTY ROADS & STATE HIGHWAYS
CURB & GUTTER SECTION



NOTE: TURNOUTS AND PRIVATE DRIVES
SHALL BE MODIFIED WHERE NECESSARY
TO MEET LOCAL CONDITIONS AS DIRECTED
BY THE ENGINEER.



 ASPHALT CONCRETE HOT MIX SURFACE
COURSE (220 LBS. PER SQ. YD.)
AGGREGATE BASE COURSE (CLASS 7)
7" COMP. DEPTH IF ASPHALT DRIVE EXIST OR
6" CONCRETE IF CONCRETE DRIVE EXIST.

 AGGREGATE BASE COURSE (CLASS 7)
9" COMP. DEPTH OR CONFORM
TO EXISTING DRIVEWAY

DETAIL FOR DRIVEWAY TURNOUTS
(COLLECTORS)


DATE	REV	DATE FILMED	DESCRIPTION
5-19-22			ISSUED

ARKANSAS STATE HIGHWAY COMMISSION
DETAILS OF DRIVEWAYS & STREET
TURNOUTS
STANDARD DRAWING DR-2






DETAILS OF W-BEAM GUARDRAIL


RAIL SECTION OF CLOSELY SIMILAR DIMENSIONS AND COMPARABLE STRENGTH MAY BE SUBSTITUTED IF APPROVED BY THE ENGINEER.




**SPLICE BOLT
POST BOLT - SAME EXCEPT LENGTH**



WOOD BLOCKOUT (W-BEAM)





NOTES:
1. SIMILAR SHAPED PLASTIC BLOCKOUTS MAY BE USED AS LONG AS THEY MEET REQUIREMENTS FOR MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).
2. DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCES.




WOOD BLOCKOUT CONNECTIONS


DETAILS OF STEEL LINE POST CONNECTIONS (W-BEAM)



STEEL POST




DETAILS OF STEEL LINE POST CONNECTIONS (W-BEAM)



WOOD BLOCKOUT CONNECTIONS

DETAILS OF WOOD LINE POST CONNECTIONS (W-BEAM)



PLASTIC BLOCKOUT CONNECTIONS

-GENERAL NOTES-

ALL BOLTS SHALL BE SUFFICIENT LENGTH TO EXTEND THROUGH THE FULL THICKNESS OF THE NUT AND NO MORE THAN 3/4" BEYOND IT.
WHERE W-BEAM GUARDRAIL CONTINUES, THE INTERMEDIATE SECTIONS SHALL HAVE A POST SPACING OF 6'-3" UNLESS OTHERWISE NOTED.

W-BEAM GUARDRAIL REPRESENTING INTERMEDIATE SECTIONS WILL BE MEASURED ALONG THE ROADWAY FACE FROM CENTERLINE OF POST TO CENTERLINE OF POST.

USE W-BEAM GUARDRAIL COMPONENTS OF SAME MATERIAL FOR ENTIRE JOB. FOR EXTENSIONS OR MODIFICATION OF EXISTING GUARDRAIL, W-BEAM GUARDRAIL COMPONENTS OF THE SAME TYPE AS THOSE EXISTING SHALL BE USED.

ANY BACKFILLING UNDER OR AROUND POST SHALL BE DAMP SAND THOROUGHLY TAMPED IN PLACE.

WOOD POSTS & WOOD BLOCKS SHALL BE EITHER DENSE NO. 1 STRUCTURAL OR BETTER 9.7f (1400 f) OR NO. 1 1350 f SOUTHERN PINE.

CONTRACTOR SHALL HAVE THE OPTION OF USING WOOD BLOCKOUTS FOR W-BEAM GUARDRAIL OR PLASTIC BLOCKOUTS, AS LONG AS BLOCKOUT USED MEETS REQUIREMENTS FOR MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) FOR W-BEAM GUARDRAIL.


DELINEATORS SHALL BE MOUNTED AT 37.5' SPACING ON THE FRONT FACE OF THE GUARDRAIL. SPACING MAY BE REDUCED IN CURVES, AS DIRECTED BY THE ENGINEER. COLOR SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES. PAYMENT FOR DELINEATORS SHALL BE CONSIDERED INCLUDED IN THE PRICE BID PER LIN. FT. FOR GUARDRAIL.

05-19-22	REVISED GENERAL NOTES, ADDED DELINEATOR LOCATION.	
11-07-19	RENUMBERED AND RENAMED	
11-16-17	REVISED GENERAL NOTES AND RAISED GUARDRAIL HEIGHT 3"	
07-14-10	RAISED HEIGHT OF GUARDRAIL 1"	
10-15-09	ADDED REFERENCE TO MASH	
04-10-03	REVISED GENERAL NOTES	
08-22-02	REVISED DIMENSION ON WOOD & PLASTIC BLOCKOUT CONNECTIONS & STEEL POST	
11-16-01	REVISED WOOD BLOCKOUT & DETAILS OF WOOD LINE POST CONNECTIONS	
03-30-00	REMOVED GUARDRAIL AT BRIDGE ENDS	
01-12-00	ADDED PLASTIC BLOCKOUT	
08-12-98	REV. BLOCKOUTS TO WOOD, DELETED CONC. POST & REV. GENERAL NOTE, DELETED DET. OF GUARDRAIL REPLACE. BEHIND CURB & DET. OF POST PLACE. IN SOLID ROCK, & ADDED DETAILS OF STEEL LINE POST CONC. REMOVED BACK-UP PLATE, REVISED HOLES IN STEEL POLES	
04-03-97	REMOVED "LAP IN DIRECTION OF TRAFFIC" NOTE & PLACED ARROWS ON WASHERS	
10-18-96	REVISED WOOD POST NOTE	
06-02-94	ADDED ALT. STEEL POST SIZE	
08-05-93	REVISED STEEL POST SIZE	8-5-93
10-01-92	REDRAWN & REVISED	10-1-92
08-15-91	REVISED WASHER NOTE	8-15-91
08-02-90	REV. GEN. NOTE & DEPTH OF ANC. POST IN ROCK	8-2-90
07-15-88	REVISED SECTION 3 & GENERAL NOTES	
03-04-88	REV. ANCHOR POST ELEV. NOTES & POST IN ROCK	780-3-4-88
10-30-87	REVISED WOOD LINE POST DETAIL	546-10-30-87
10-09-87	REDRAWN & REVISED	802-10-9-87
DATE	REVISION	FILMED


ARKANSAS STATE HIGHWAY COMMISSION

GUARDRAIL DETAILS

STANDARD DRAWING GR-6




WASHER PLATE




BASE PLATE

Note: Bolts, nuts, washers and plates shall be galvanized in accordance with Section 807 of the Standard Specifications.



FOR DESIGN SPEEDS OF 50 MPH OR LESS

ALIGN FACE OF GUARDRAIL WITH FACE OF CURB.





FOR DESIGN SPEEDS OF 55 MPH OR MORE

PLACE GUARDRAIL POSTS AGAINST BACK OF CURB.


DETAIL OF GUARDRAIL PLACEMENT BEHIND CURB (W-BEAM)

FOR DESIGN SPEEDS OF 50 MPH OR LESS ALL CURB FACES, AS SHOWN ON STD. DRWG. CG-1, MAY BE USED. FOR DESIGN SPEEDS OF 55 MPH OR MORE TYPE "E" CURB FACE SHALL BE USED.




Plan View Steel Posts

Either hole configuration acceptable



Plan View Wood Posts

Either hole configuration acceptable



Notes: For overlying soil depths (A) ranging from 0 to 18", the depth of required drilling (B) is equal to 24".


Zone A: Backfill according to Section 617.03(a).

Zone B: Backfill hole in 6" lifts with material meeting the requirements of Section 802.02(c) - Alternate gradation. Compact to 95% maximum dry density per ASTM D-698.


Notes: For overlying soil depths (A) ranging from 18" to 44", the depth of required drilling (B) is equal to either 12" or 44" minus the depth of soil whichever is less.

Zone A & B: Backfill according to Section 617.03(a).


DETAIL OF POST PLACEMENT IN SOLID ROCK (W-BEAM)



SECTION A-A



DETAIL OF CONNECTION



PLAN LAYOUT OF TYPE A GUARDRAIL AT LOW-FILL CULVERTS

NOTE: THIS DETAIL IS TO BE USED ONLY WHEN THE COVER OVER THE CULVERT DOES NOT PERMIT FULL EMBEDMENT OF GUARDRAIL POSTS AS SHOWN ON STD. DRWG. GR-6.


NOTE: WHEN POSSIBLE, POSTS SHALL BE SPACED TO AVOID INTERIOR AND EXTERIOR WALLS OF CULVERT. WHEN THIS IS NOT POSSIBLE AND POSTS MUST BE INSTALLED OVER AN INTERIOR OR EXTERIOR WALL, ANCHOR BOLTS SHALL BE INSTALLED BY DRILLING AND EPOXYING USING METHODS AND MATERIALS APPROVED BY THE ENGINEER.

DATE	REVISION	FILED
11-07-19	RENUMBERED, RENAMED, REVISED REFERENCE	
11-16-17	REVISED GUARDRAIL HEIGHT	
07-14-10	RAISED HEIGHT OF GUARDRAIL 1"	
04-12-07	REVISED DETAIL OF GUARDRAIL PLACEMENT BEHIND CURB	
11-10-05	ADDED GUARDRAIL PLACEMENT BEHIND CURB; REVISED DETAIL OF CONNECTION	
11-18-04	REVISED POST PLACEMENT IN ROCK & CULVERT CONNECTION DETAILS. ADDED DETAIL FOR GUARDRAIL PLACEMENT AT LOW-FILL CULVERTS	
03-30-00	REMOVED CONCRETE INSERT ANCHOR	
08-12-98	CHANGED STEEL SPACER BLOCK TO WOOD BLOCKOUT, ADDED DET. OF GUARDRAIL CONNECTION TO R.C. BOX CULVERT, DELETED DET. OF STEEL LINE POST CONN. & ADDED DET. OF GUARDRAIL PLACE. BEHIND CURB & DET. OF POSTPLACE. IN SOLID ROCK	
04-03-96	PLACED ARROWS AT CUT STEEL WASHERS	4-3-96
10-18-96	REV. ASTM REF. TO AASHTO	
11-22-95	ADDED OPTIONAL HOLES	
06-02-94	REVISED ALTERNATE POST SIZE	
08-05-93	REVISED STEEL POST SIZE	
10-01-92	REDRAWN & REVISED	10-1-92
08-02-90	DEL. WASHER ON ANCHOR ASSEMBLY	8-2-90
07-15-88	CONFORMED TO 1988 SPECS	
03-04-88	REVISED ANCHOR NOTE	
10-30-87	REVISED ANCHOR ASSEMBLY	712-10-30-87
10-30-87	REVISED PLACEMENT BEHIND CURB	547-10-30-87
10-09-87	REDRAWN & REVISED	803-10-9-87


ARKANSAS STATE HIGHWAY COMMISSION

GUARDRAIL DETAILS


STANDARD DRAWING GR-7



METHODS OF INSTALLATION OF GUARDRAIL AT LESS THAN FULL SHOULDER WIDTH BRIDGES USING GUARDRAIL TERMINAL (TYPE 2)



METHOD OF INSTALLATION OF GUARDRAIL AT FULL SHOULDER WIDTH BRIDGES USING GUARDRAIL TERMINAL (TYPE 2)




METHOD OF INSTALLATION OF GUARDRAIL USING GUARDRAIL TERMINAL (TYPE 1) (FULL SHOULDER WIDTH OR LESS BRIDGES)

DATE	REVISION	DATE	FILM
11-07-19	RENUMBERED AND RENAMED		
4-17-08	REVISED LAYOUTS		
11-10-05	REMOVED GUARDRAIL NOTES AND DETAILS		
11-16-01	DELETED NOTE-METHOD OF INSTALLATION OF GUARDRAIL USING GUARDRAIL TERM. (TY. 1)		
1-12-00	ADDED CONSTRUCTION NOTE	1-12-00	
6-26-97	REVISED LAYOUT		
10-1-92	REDRAWN & REVISED	10-1-92	
10-9-87	ADDED NOTE		
10-9-87	REDRAWN & REVISED		



ARKANSAS STATE HIGHWAY COMMISSION

GUARDRAIL DETAILS



STANDARD DRAWING GR-8




NOTE: NORMAL SECTION TO BE WIDENED APPROX. 5'-6" EACH SIDE TO SUPPORT GUARDRAIL.



DETAILS SHOWING POSITION OF GUARDRAIL ON HIGHWAY



DETAILS OF WIDENING FOR GUARDRAIL




METHOD OF INSTALLATION OF GUARDRAIL AT FIXED OBSTACLE

DATE	REVISION	DATE FILM
11-07-19	RENUMBERED AND RENAMED	
4-17-08	MINOR REVISION	
11-10-05	DRAWN	


ARKANSAS STATE HIGHWAY COMMISSION

GUARDRAIL DETAILS


STANDARD DRAWING GR-9




SPECIAL END SHOE




SECTION THRU THRIE BEAM RAIL



THRIE BEAM RAIL




TRANSITION SECTION




ATTACH BLOCKOUT TO POST USING 3/8" DIA. HEX HEAD BOLTS WITH 1/2" O.D. CUT STEEL WASHERS AND NUT.

STRUCTURAL STEEL TUBING BLOCKOUT DETAIL




HOLE PUNCHING DETAIL FOR STEEL POST & WOOD OR PLASTIC BLOCKOUTS

NOTE: BLOCKS SHALL BE THE SAME TYPE THROUGHOUT THE PROJECT LIMITS.



CONNECTOR PLATE

CONNECTOR PLATE SHALL BE AASHTO M270, GR. 36 AND SHALL BE GALVANIZED AFTER FABRICATION. GALVANIZING SHALL CONFORM TO SUBSECTION 807.19 OF THE STANDARD SPECIFICATIONS. CONNECTOR PLATE TO BE BOLTED TO SPECIAL END SHOE USING 7/8" DIA. HIGH STRENGTH BOLTS, WITH THE HEADS PLACED ON THE TRAFFIC FACE. WASHERS SHALL BE USED UNDER THE HEAD AND NUT. BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED AND SHALL CONFORM TO SUBSECTION 807.06.




THRIE BEAM RAIL SPLICE AT POST

GENERAL NOTES:


- THE THRIE BEAM RAIL, SPECIAL END SHOE, AND THE TRANSITION SECTION SHALL BE MADE OF STEEL AND SHALL BE 12 GAGE. ZINC COATING SHALL BE TYPE I.
- RAIL POSTS SHALL BE SET PERPENDICULAR TO THE ROADWAY PROFILE GRADE AND VERTICALLY IN CROSS SECTION.
- ALL BOLTS SHALL BE SUFFICIENT LENGTH TO EXTEND THROUGH THE FULL THICKNESS OF THE NUT AND NO MORE THAN 3"4" BEYOND IT.
- ALL LAP SPLICES, INCLUDING SPECIAL END SHOES, SHALL BE MADE IN THE DIRECTION SHOWN ON STANDARD DRAWINGS GR-8 & GR-13.
- REFER TO STD. DRWG. GR-II FOR POST DETAILS.
- USE THRIE BEAM GUARDRAIL COMPONENTS OF SAME MATERIAL FOR ENTIRE JOB.
- THRIE BEAM POSTS SHALL BE SAME MATERIAL AS W-BEAM POSTS FOR ENTIRE JOB.
- WOOD POSTS & WOOD BLOCKS SHALL BE EITHER DENSE NO. 1 STRUCTURAL OR BETTER 9.7F (1400 F) OR NO. 1 1350 F SOUTHERN PINE.

DATE	REVISION	FILMED
11-07-19	RENAMED AND REVISED REFERENCES	
11-16-17	REVISED TRANSITION SECTION, GUARD RAIL HEIGHT, AND GENERAL NOTES; MOVED THRIE BEAM GUARD RAIL CONNECTIONS AT BRIDGE ENDS TO STD. DRWG. GR-12	
07-14-10	RAISED HEIGHT OF W-BEAM 1"	
11-29-07	ADDED PLASTIC BLOCKOUTS	
11-10-05	ADDED NOTE FOR ATTACHING STEEL BLOCKOUT	
11-18-04	REVISED GENERAL NOTES	
10-9-03	REVISED GENERAL NOTES	
04-10-03	REVISED GENERAL NOTES	
08-22-02	REVISED NOTE (2)	
06-29-00	MOVED DIMENSION LINES	
05-18-00	ADDED NOTE	
03-30-00	DRAWN & ISSUED	


ARKANSAS STATE HIGHWAY COMMISSION
GUARDRAIL DETAILS
 STANDARD DRAWING GR-10




THRIE BEAM RAIL WITH STEEL TUBING BLOCKOUT
AND STEEL POST
POSTS 1-7




W-BEAM TO THRIE BEAM TRANSITION RAIL
WITH WOOD OR PLASTIC BLOCKOUT AND STEEL POST
POST 8



THRIE BEAM RAIL
WITH WOOD OR PLASTIC
BLOCKOUTS & WOOD POSTS
POSTS 1-6



THRIE BEAM RAIL
WITH WOOD OR PLASTIC
BLOCKOUT & WOOD POST
POST 7




W-BEAM TO THRIE BEAM
TRANSITION RAIL WITH WOOD OR
PLASTIC BLOCKOUT & WOOD POST
POST 8


GENERAL NOTES:
RAIL POSTS SHALL BE SET PERPENDICULAR TO THE ROADWAY PROFILE GRADE AND
VERTICALLY IN CROSS SECTION.

WOOD POSTS & WOOD BLOCKS SHALL BE EITHER DENSE NO. 1 STRUCTURAL OR
BETTER 9.7f (1400 f) OR NO. 1 1350 f SOUTHERN PINE.


DATE	REVISION	FILMED	ARKANSAS STATE HIGHWAY COMMISSION
11-07-19	RENAMED		GUARDRAIL DETAILS
11-16-17	REVISED GUARDRAIL HEIGHT, CHANGED STD. DWG. NUMBER FROM GR-10A TO GR-II		
07-14-10	REVISED POST 8 DIMENSIONS		STANDARD DRAWING GR-II
11-29-07	ADDED PLASTIC BLOCKOUTS		
08-22-02	REVISED LIP CURB NOTE		
03-30-00	DRAWN & ISSUED		



ELEVATION



PLAN



PLAN

- (1) VERIFY BOLT SPACING FROM RAIL TRANSITION PRODUCER.
- (2) REFER TO APPROACH GUTTER DETAILS.
- (3) LENGTH OF BLOCKOUT ON POST 8 TO BE MODIFIED TO FIT RAIL WIDTH.

THRIE BEAM GUARDRAIL CONNECTION AT BRIDGE ENDS

GENERAL NOTES:
 THE THRIE BEAM RAIL, SPECIAL END SHOE, AND THE TRANSITION SECTION SHALL BE MADE OF STEEL AND SHALL BE 12 GAGE. ZINC COATING SHALL BE TYPE I.
 RAIL POSTS SHALL BE SET PERPENDICULAR TO THE ROADWAY PROFILE GRADE AND VERTICALLY IN CROSS SECTION.
 ALL BOLTS SHALL BE SUFFICIENT LENGTH TO EXTEND THROUGH THE FULL THICKNESS OF THE NUT AND NO MORE THAN 3/4" BEYOND IT.
 ALL LAP SPLICES, INCLUDING SPECIAL END SHOES, SHALL BE MADE IN THE DIRECTION SHOWN ON STANDARD DRAWINGS GR-8 & GR-13.
 REFER TO STD. DRWG. GR-II FOR POST DETAILS.
 USE THRIE BEAM GUARDRAIL COMPONENTS OF SAME MATERIAL FOR ENTIRE JOB.
 THRIE BEAM POSTS SHALL BE SAME MATERIAL AS W-BEAM POSTS FOR ENTIRE JOB.
 POSTS SHALL NOT BE PLACED AT SPLICE LOCATIONS ALONG W-BEAM RAILS.
 WOOD POSTS & WOOD BLOCKS SHALL BE EITHER DENSE NO. 1 STRUCTURAL OR BETTER 9.7F (1400 F) OR NO. 1 1350 F SOUTHERN PINE.

			ARKANSAS STATE HIGHWAY COMMISSION
			GUARDRAIL DETAILS
			STANDARD DRAWING GR-12
05-14-20	REVISED NOTES		
11-07-19	RENAMED & REVISED REFERENCES		
11-16-17	RE-DRAWN FROM STD. DWG. GR-10 & ISSUED		
DATE	REVISION		FILMED

INSTALLATION TYPE	•• MATERIAL REQUIREMENTS FOR STRUCTURAL BACKFILL AND STRUCTURAL BEDDING
TYPE 2	•SELECTED MATERIALS (CLASS SM-1, SM-2 OR SM-4)

- AGGREGATE BASE COURSE (CLASS 4, 5, 6, OR 7) MAY BE USED IN LIEU OF SELECTED MATERIAL.
 - SM3 WILL NOT BE ALLOWED.
 - STRUCTURAL BEDDING MATERIAL SHALL HAVE A MAXIMUM PARTICLE SIZE OF 1/2 INCH. STRUCTURAL BACKFILL MATERIAL SHALL BE FREE OF ORGANIC MATERIAL, STONES LARGER THAN 1.50 INCH IN GREATEST DIMENSION, OR FROZEN LUMPS.
- STRUCTURAL BACKFILL AND STRUCTURAL BEDDING MATERIAL WILL NOT BE PAID FOR SEPARATELY, BUT COMPENSATION WILL BE CONSIDERED TO BE INCLUDED IN THE PRICE BID PER LINEAR FOOT OF HDPE PIPE.

MINIMUM TRENCH WIDTH BASED ON FILL HEIGHT "H"

PIPE DIAMETER	TRENCH WIDTH (FEET)	
	"H" < 10'-0"	"H" >OR= 10'-0"
18"	4'-6"	4'-6"
24"	5'-0"	6'-0"
30"	5'-6"	7'-6"
36"	6'-0"	9'-0"
42"	7'-0"	10'-6"
48"	8'-0"	12'-0"

NOTE:
 18" MIN. (18" - 30" DIAMETERS)
 24" MIN. (36" - 48" DIAMETERS)
 MINIMUM COVER VALUES, "H" SHALL INCLUDE A MINIMUM 12" OF PAVEMENT AND/OR BASE.


MULTIPLE INSTALLATION OF HIGH DENSITY POLYETHYLENE PIPES

PIPE DIAMETER	CLEAR DISTANCE BETWEEN PIPES
18"	1'-6"
24"	2'-0"
30"	2'-6"
36"	3'-0"
42"	3'-6"
48"	4'-0"

MINIMUM COVER FOR CONSTRUCTION LOADS

PIPE DIAMETER	MIN. COVER (FEET) FOR INDICATED CONSTRUCTION LOADS			
	18.0-50.0 (KIPS)	50.0-75.0 (KIPS)	75.0-110.0 (KIPS)	110.0-175.0 (KIPS)
36" OR LESS	2'-0"	2'-6"	3'-0"	3'-0"
42" OR GREATER	3'-0"	3'-0"	3'-6"	4'-0"

MINIMUM COVER SHALL BE MEASURED FROM TOP OF PIPE TO TOP OF THE MAINTAINED CONSTRUCTION ROADWAY SURFACE. THE SURFACE SHALL BE MAINTAINED.



TYPE 2 EMBANKMENT AND TRENCH INSTALLATIONS

1. STRUCTURAL BACKFILL, EMBANKMENT, AND OUTER STRUCTURAL BEDDING MATERIAL SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.

CONSTRUCTION SEQUENCE

1. PLACE STRUCTURAL BEDDING MATERIAL TO GRADE. DO NOT COMPACT.
2. INSTALL PIPE TO GRADE.
3. COMPACT STRUCTURAL BEDDING OUTSIDE THE MIDDLE THIRD OF THE PIPE.
4. THE STRUCTURAL BACKFILL SHALL BE PLACED AND COMPACTED IN LAYERS NOT EXCEEDING 8". THE LAYERS SHALL BE BROUGHT UP EVENLY AND SIMULTANEOUSLY TO THE ELEVATION OF THE MINIMUM COVER.
5. PIPE INSTALLATION MAY REQUIRE THE USE OF RESTRAINTS, WEIGHTING OR OTHER APPROVED METHODS IN ORDER TO HELP MAINTAIN GRADE AND ALIGNMENT.

- LEGEND -

H = FILL HEIGHT (FT.)
 Ø = OUTSIDE DIAMETER OF PIPE
 MAX. = MAXIMUM
 MIN. = MINIMUM

==== = STRUCTURAL BACKFILL MATERIAL
 // // // = UNDISTURBED SOIL

GENERAL NOTES

1. PIPE SHALL CONFORM TO AASHTO M294, TYPE S. INSTALLATION SHALL CONFORM TO JOB SPECIAL PROVISION "PLASTIC PIPE" AND SECTION 606 OF THE STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION).
2. PLASTIC PIPE CULVERT DESIGN SHALL CONFORM TO AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, FIFTH EDITION (2010) WITH 2010 INTERIMS.
3. THE MAXIMUM ALLOWABLE TRENCH WIDTH SHALL BE THE MINIMUM WIDTH PLUS A SUFFICIENT WIDTH TO ENSURE WORKING ROOM TO PROPERLY AND SAFELY PLACE AND COMPACT HAUNCHING AND OTHER BACKFILL MATERIAL.
4. IMPERVIOUS MATERIAL SHOULD BE PLACED AS DIRECTED BY THE ENGINEER AT THE ENDS OF THE CULVERT TO PREVENT LOSS OF STRUCTURAL BEDDING WHEN PERVIOUS MATERIAL IS USED FOR STRUCTURAL BEDDING AND/OR BACKFILL.
5. WHEN DIRECTED BY THE ENGINEER, UNSUITABLE MATERIAL THAT IS ENCOUNTERED AT THE BOTTOM OF THE EXCAVATED TRENCH (BELOW THE AREA IDENTIFIED AS "STRUCTURAL BEDDING" ABOVE) WILL BE EXCAVATED AND REPLACED WITH SELECTED PIPE BEDDING. THE QUANTITY OF MATERIAL REQUIRED TO BACKFILL THE UNDERCUT AREA UP TO THE SELECTED PIPE BEDDING PAY LIMIT DESIGNATED ABOVE WILL BE MEASURED AND PAID FOR AS "SELECTED PIPE BEDDING."
6. WHEN THE EXISTING MATERIAL EXCAVATED FOR THE PIPE TRENCH IS DETERMINED BY THE ENGINEER TO BE UNSUITABLE FOR BACKFILLING THE PIPE (ABOVE THE AREA IDENTIFIED ABOVE AS STRUCTURAL BACKFILL), BORROW MATERIAL OR MATERIAL FROM THE ROADWAY EXCAVATION WILL BE USED TO BACKFILL THE PIPE. IF SUITABLE MATERIAL IS NOT AVAILABLE, THE ENGINEER MAY AUTHORIZE THE USE OF "SELECTED PIPE BACKFILL."
7. FOR PIPE TYPES THAT ARE NOT SMOOTH ON THE OUTSIDE (CORRUGATED OR PROFILE WALLS), BACKFILL GRADATIONS SHOULD BE SELECTED THAT WILL PERMIT THE FILLING OF THE CORRUGATION OR PROFILE VALLEY.
8. HIGH DENSITY POLYETHYLENE PIPES OF DIAMETERS OTHER THAN SHOWN WILL NOT BE ALLOWED.
9. JOINTS FOR HDPE PIPE SHALL MEET THE REQUIREMENTS FOR SOIL TIGHTNESS AS SPECIFIED IN AASHTO SECTION 26.4.2.4 AND 30.4.2 "AASHTO LRFD BRIDGE CONSTRUCTION SPECIFICATIONS." JOINTS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.

DATE	REVISION	DATE FILMED
2-27-14	REVISED GENERAL NOTE 1.	
12-15-11	REVISED GENERAL NOTES & MINIMUM COVER NOTE	
11-17-10	ISSUED	

ARKANSAS STATE HIGHWAY COMMISSION
**PLASTIC PIPE CULVERT
 (HIGH DENSITY POLYETHYLENE)**
 STANDARD DRAWING PCP-1

INSTALLATION TYPE	** MATERIAL REQUIREMENTS FOR STRUCTURAL BACKFILL AND STRUCTURAL BEDDING
TYPE 2	•SELECTED MATERIALS (CLASS SM-1, SM-2, OR SM-4)

- AGGREGATE BASE COURSE (CLASS 4, 5, 6, OR 7) MAY BE USED IN LIEU OF SELECTED MATERIAL. SM3 WILL NOT BE ALLOWED.
 - STRUCTURAL BEDDING MATERIAL SHALL HAVE A MAXIMUM PARTICLE SIZE OF 1 INCH. STRUCTURAL BACKFILL MATERIAL SHALL BE FREE OF ORGANIC MATERIAL, STONES LARGER THAN 1.50 INCH IN GREATEST DIMENSION, OR FROZEN LUMPS.
- STRUCTURAL BACKFILL AND STRUCTURAL BEDDING MATERIAL WILL NOT BE PAID FOR SEPARATELY, BUT COMPENSATION WILL BE CONSIDERED TO BE INCLUDED IN THE PRICE BID PER LINEAR FOOT OF PVC PIPE.

MINIMUM TRENCH WIDTH BASED ON FILL HEIGHT "H"

PIPE DIAMETER	TRENCH WIDTH (FEET)	
	"H" < 10'-0"	"H" > OR = 10'-0"
18"	4'-6"	4'-6"
24"	5'-0"	6'-0"
30"	5'-6"	7'-6"
36"	6'-0"	9'-0"


MULTIPLE INSTALLATION OF PVC PIPES

PIPE DIAMETER	CLEAR DISTANCE BETWEEN PIPES
18"	1'-6"
24"	2'-0"
30"	2'-6"
36"	3'-0"

MAXIMUM FILL HEIGHT BASED ON STRUCTURAL BACKFILL

PIPE DIAMETER	"H"
18"	45'-0"
24"	45'-0"
30"	40'-0"
36"	40'-0"

- ① NOTE:
12" MIN. (18" - 36" DIAMETERS) MINIMUM COVER VALUE, "H" SHALL INCLUDE A MINIMUM 12" OF PAVEMENT AND/OR BASE.



TYPE 2 EMBANKMENT AND TRENCH INSTALLATIONS

1. STRUCTURAL BACKFILL, EMBANKMENT, AND OUTER STRUCTURAL BEDDING MATERIAL SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.

CONSTRUCTION SEQUENCE

1. PLACE STRUCTURAL BEDDING MATERIAL TO GRADE. DO NOT COMPACT.
2. INSTALL PIPE TO GRADE.
3. COMPACT STRUCTURAL BEDDING OUTSIDE THE MIDDLE THIRD OF THE PIPE.
4. THE STRUCTURAL BACKFILL SHALL BE PLACED AND COMPACTED IN LAYERS NOT EXCEEDING 8". THE LAYERS SHALL BE BROUGHT UP EVENLY AND SIMULTANEOUSLY TO THE ELEVATION OF THE MINIMUM COVER.
5. PIPE INSTALLATION MAY REQUIRE THE USE OF RESTRAINTS, WEIGHTING OR OTHER APPROVED METHODS IN ORDER TO HELP MAINTAIN GRADE AND ALIGNMENT.

- LEGEND -

H = FILL HEIGHT (FT.)
D_o = OUTSIDE DIAMETER OF PIPE
MAX. = MAXIMUM
MIN. = MINIMUM

==== = STRUCTURAL BACKFILL MATERIAL

||||| = UNDISTURBED SOIL

GENERAL NOTES

1. PIPE SHALL CONFORM TO ASTM F949, CELL CLASS I2454. INSTALLATION SHALL CONFORM TO JOB SPECIAL PROVISION "PLASTIC PIPE" AND SECTION 606 OF THE STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION).
2. PLASTIC PIPE CULVERT DESIGN SHALL CONFORM TO AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, FIFTH EDITION (2010) WITH 2010 INTERIMS.
3. THE MAXIMUM ALLOWABLE TRENCH WIDTH SHALL BE THE MINIMUM WIDTH PLUS A SUFFICIENT WIDTH TO ENSURE WORKING ROOM TO PROPERLY PLACE AND COMPACT HAUNCHING AND OTHER BACKFILL MATERIAL.
4. IMPERVIOUS MATERIAL SHOULD BE PLACED AS DIRECTED BY THE ENGINEER AT THE ENDS OF THE CULVERT TO PREVENT LOSS OF STRUCTURAL BEDDING WHEN PERVIOUS MATERIAL IS USED FOR STRUCTURAL BEDDING AND/OR BACKFILL.
5. WHEN DIRECTED BY THE ENGINEER, UNSUITABLE MATERIAL THAT IS ENCOUNTERED AT THE BOTTOM OF THE EXCAVATED TRENCH (BELOW THE AREA IDENTIFIED AS "STRUCTURAL BEDDING" ABOVE) WILL BE EXCAVATED AND REPLACED WITH SELECTED PIPE BEDDING. THE QUANTITY OF MATERIAL REQUIRED TO BACKFILL THE UNDERCUT AREA UP TO THE SELECTED PIPE BEDDING PAY LIMIT DESIGNATED ABOVE WILL BE MEASURED AND PAID FOR AS "SELECTED PIPE BEDDING."
6. WHEN THE EXISTING MATERIAL EXCAVATED FOR THE PIPE TRENCH IS DETERMINED BY THE ENGINEER TO BE UNSUITABLE FOR BACKFILLING THE PIPE (ABOVE THE AREA IDENTIFIED ABOVE AS STRUCTURAL BACKFILL), BORROW MATERIAL OR MATERIAL FROM THE ROADWAY EXCAVATION WILL BE USED TO BACKFILL THE PIPE. IF SUITABLE MATERIAL IS NOT AVAILABLE, THE ENGINEER MAY AUTHORIZE THE USE OF "SELECTED PIPE BACKFILL."
7. FOR PIPE TYPES THAT ARE NOT SMOOTH ON THE OUTSIDE (CORRUGATED OR PROFILE WALLS), BACKFILL GRADATIONS SHOULD BE SELECTED THAT WILL PERMIT THE FILLING OF THE CORRUGATED OR PROFILE VALLEY.
8. PVC PIPES OF DIAMETERS OTHER THAN SHOWN WILL NOT BE ALLOWED.
9. JOINTS FOR PVC PIPE SHALL MEET THE REQUIREMENTS FOR SOIL TIGHTNESS AS SPECIFIED IN AASHTO SECTION 26.4.2.4 AND 30.4.2 "AASHTO LRFD BRIDGE CONSTRUCTION SPECIFICATIONS." JOINTS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.

DATE	REVISION	DATE FILMED
2-27-14	REVISED GENERAL NOTE 1.	
12-15-11	REV GENERAL NOTES & MINIMUM COVER NOTE; DELETED SM3 MATERIAL	
11-17-10	ISSUED	

ARKANSAS STATE HIGHWAY COMMISSION

PLASTIC PIPE CULVERT
(PVC F949)

STANDARD DRAWING PCP-2



INSTALLATION TYPE	**MATERIAL REQUIREMENTS FOR STRUCTURAL BACKFILL AND STRUCTURAL BEDDING
TYPE 1	AGGREGATE BASE COURSE (CLASS 4, 5, 6, OR 7)
TYPE 2	*SELECTED MATERIALS (CLASS SM-1, SM-2 OR SM-4) OR TYPE 1 INSTALLATION MATERIAL

* SM3 WILL NOT BE ALLOWED.

** STRUCTURAL BEDDING MATERIAL SHALL HAVE A MAXIMUM PARTICLE SIZE OF 1/2 INCH. STRUCTURAL BACKFILL MATERIAL SHALL BE FREE OF ORGANIC MATERIAL, STONES LARGER THAN 1.50 INCH IN GREATEST DIMENSION, OR FROZEN LUMPS.

STRUCTURAL BACKFILL AND STRUCTURAL BEDDING MATERIAL WILL NOT BE PAID FOR SEPARATELY, BUT COMPENSATION WILL BE CONSIDERED TO BE INCLUDED IN THE PRICE BID PER LINEAR FOOT OF POLYPROPYLENE PIPE.

MINIMUM TRENCH WIDTH BASED ON FILL HEIGHT "H"

PIPE DIAMETER	TRENCH WIDTH (FEET)	
	"H" < 10'-0"	"H" >OR= 10'-0"
18"	4'-6"	4'-6"
24"	5'-0"	6'-0"
30"	5'-6"	7'-6"
36"	6'-0"	9'-0"
42"	7'-0"	10'-6"
48"	8'-0"	12'-0"
60"	10'-0"	15'-0"

① NOTE:
12" MIN. (18" - 42" DIAMETERS)
24" MIN. (60" DIAMETER)
MINIMUM COVER VALUES, "H" SHALL INCLUDE A MINIMUM 12" OF PAVEMENT AND/OR BASE.

MINIMUM COVER FOR CONSTRUCTION LOADS

PIPE DIAMETER	② MIN. COVER (FEET) FOR INDICATED CONSTRUCTION LOADS			
	18.0-50.0 (KIPS)	50.0-75.0 (KIPS)	75.0-110.0 (KIPS)	110.0-150.0 (KIPS)
36" OR LESS	2'-0"	2'-6"	3'-0"	3'-0"
42" OR GREATER	3'-0"	3'-0"	3'-6"	4'-0"

② MINIMUM COVER SHALL BE MEASURED FROM TOP OF PIPE TO TOP OF THE MAINTAINED CONSTRUCTION ROADWAY SURFACE. THE SURFACE SHALL BE MAINTAINED.

MULTIPLE INSTALLATION OF POLYPROPYLENE PIPES


PIPE DIAMETER	CLEAR DISTANCE BETWEEN PIPES
18"	1'-6"
24"	2'-0"
30"	2'-6"
36"	3'-0"
42"	3'-6"
48"	4'-0"
60"	5'-0"

GENERAL NOTES

- PIPE SHALL CONFORM TO AASHTO M330, TYPE S. INSTALLATION SHALL CONFORM TO JOB SPECIAL PROVISION "PLASTIC PIPE" AND SECTION 606 OF THE STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION).
- PLASTIC PIPE CULVERT DESIGN SHALL CONFORM TO AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SIXTH EDITION (2012) WITH 2013 INTERIMS.
- THE MAXIMUM ALLOWABLE TRENCH WIDTH SHALL BE THE MINIMUM WIDTH PLUS A SUFFICIENT WIDTH TO ENSURE WORKING ROOM TO PROPERLY AND SAFELY PLACE AND COMPACT HAUNCHING AND OTHER BACKFILL MATERIAL.
- IMPERVIOUS MATERIAL SHOULD BE PLACED AS DIRECTED BY THE ENGINEER AT THE ENDS OF THE CULVERT TO PREVENT LOSS OF STRUCTURAL BEDDING WHEN PERVIOUS MATERIAL IS USED FOR STRUCTURAL BEDDING AND/OR BACKFILL.
- WHEN DIRECTED BY THE ENGINEER, UNSUITABLE MATERIAL THAT IS ENCOUNTERED AT THE BOTTOM OF THE EXCAVATED TRENCH (BELOW THE AREA IDENTIFIED AS "STRUCTURAL BEDDING" ABOVE) WILL BE EXCAVATED AND REPLACED WITH SELECTED PIPE BEDDING. THE QUANTITY OF MATERIAL REQUIRED TO BACKFILL THE UNDERCUT AREA UP TO THE SELECTED PIPE BEDDING PAY LIMIT DESIGNATED ABOVE WILL BE MEASURED AND PAID FOR AS "SELECTED PIPE BEDDING."
- WHEN THE EXISTING MATERIAL EXCAVATED FOR THE PIPE TRENCH IS DETERMINED BY THE ENGINEER TO BE UNSUITABLE FOR BACKFILLING THE PIPE (ABOVE THE AREA IDENTIFIED ABOVE AS STRUCTURAL BACKFILL), BORROW MATERIAL OR MATERIAL FROM THE ROADWAY EXCAVATION WILL BE USED TO BACKFILL THE PIPE. IF SUITABLE MATERIAL IS NOT AVAILABLE, THE ENGINEER MAY AUTHORIZE THE USE OF "SELECTED PIPE BACKFILL."
- FOR PIPE TYPES THAT ARE NOT SMOOTH ON THE OUTSIDE (CORRUGATED OR PROFILE WALLS), BACKFILL GRADATIONS SHOULD BE SELECTED THAT WILL PERMIT THE FILLING OF THE CORRUGATION OR PROFILE VALLEY.
- POLYPROPYLENE PIPES OF DIAMETERS OTHER THAN SHOWN WILL NOT BE ALLOWED.
- JOINTS FOR POLYPROPYLENE PIPE SHALL MEET THE REQUIREMENTS FOR SOIL TIGHTNESS AS SPECIFIED IN SECTION 26.4.2.4 AND 30.4.2 OF THE AASHTO LRFD BRIDGE CONSTRUCTION SPECIFICATIONS 3RD EDITION (2010) WITH 2012 INTERIMS. JOINTS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.

MAXIMUM HEIGHT OF FILL "H"

PIPE DIAMETER	INSTALLATION TYPE	
	TYPE 1	TYPE 2
18"	18'	14'
24"	16'	12'
30"	18'	14'
36"	16'	12'
42"	18'	13'
48"	15'	11'
60"	17'	12'



EMBANKMENT AND TRENCH INSTALLATIONS

1. STRUCTURAL BACKFILL, EMBANKMENT, AND OUTER STRUCTURAL BEDDING MATERIAL SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.

CONSTRUCTION SEQUENCE

- PLACE STRUCTURAL BEDDING MATERIAL TO GRADE. DO NOT COMPACT.
- INSTALL PIPE TO GRADE.
- COMPACT STRUCTURAL BEDDING OUTSIDE THE MIDDLE THIRD OF THE PIPE.
- THE STRUCTURAL BACKFILL SHALL BE PLACED AND COMPACTED IN LAYERS NOT EXCEEDING 8". THE LAYERS SHALL BE BROUGHT UP EVENLY AND SIMULTANEOUSLY TO THE ELEVATION OF THE MINIMUM COVER.
- PIPE INSTALLATION MAY REQUIRE THE USE OF RESTRAINTS, WEIGHTING OR OTHER APPROVED METHODS IN ORDER TO HELP MAINTAIN GRADE AND ALIGNMENT.

- LEGEND -

H = FILL HEIGHT (FT.)
D_o = OUTSIDE DIAMETER OF PIPE
MAX. = MAXIMUM
MIN. = MINIMUM

==== = STRUCTURAL BACKFILL MATERIAL
===== = UNDISTURBED SOIL


DATE	REVISION	DATE FILMED
02-27-20	REVISED	
11-07-19	ISSUED	

ARKANSAS STATE HIGHWAY COMMISSION


PLASTIC PIPE CULVERT
(POLYPROPYLENE)

STANDARD DRAWING PCP-3






CONCRETE PAVEMENT




ASPHALT PAVEMENT


BROKEN LINE STRIPING




SOLID LINE STRIPING ON CONCRETE PAVEMENT



SOLID LINE STRIPING ON ASPHALT PAVEMENT




ASPHALT PAVEMENT




CONCRETE PAVEMENT

STRIPING AT ADJACENT NO PASSING LANES




YIELD LINE DETAIL




CROSSWALK AND STOP LINE DETAILS

- NOTES:
- REFER TO THE STRIPING DETAILS FOR PAVEMENT MARKING LINE WIDTHS.
 - THIS DRAWING SHALL BE USED IN CONJUNCTION WITH THE LATEST REVISED ADDITION OF THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES."
 - RAISED PAVEMENT MARKERS SHALL BE PLACED ON AN 80 FEET SPACING UNLESS OTHERWISE SHOWN IN THE PLANS.



PAVEMENT EDGE LINE MARKING



NOTE:
THE RED LENS OF THE TYPE II R.P.M. SHALL FACE THE INCORRECT TRAFFIC MOVEMENT.

NOTE:
DIMENSIONS SHOWN FOR RAISED PAVEMENT MARKERS ARE TYPICAL. THE CONTRACTOR MAY SUBSTITUTE SIMILAR MARKERS WITH THE APPROVAL OF THE ENGINEER. REQUESTING APPROVAL FOR SIMILAR MARKERS MAY BE MADE BY REFERRING TO THE ARDOT QUALIFIED PRODUCTS LIST.

DETAIL OF STANDARD RAISED PAVEMENT MARKERS


DATE	REVISION	FILMED
2-27-20	REVISED STOP LINE DETAILS	
6-1-17	ADDED YIELD LINE DETAIL	
5-12-16	REVISED LINE WIDTHS, SPACING, & NOTES	
9-12-13	REVISED DETAIL OF STANDARD RAISED PAVEMENT MARKERS	
11-17-10	REVISED GENERAL NOTES & REMOVED PLOWABLE PVMT MRKRS	
11-18-04	REVISED NOTE 2 & GENERAL NOTES	
8-22-02	ADDED CROSSWALK & STOPBAR DTL.	
7-02-98	ADDED DETAILS OF STD. RAISED PAV'T. MARKERS	
4-26-96	REV. NOTES 3&4; ADDED R.P.M.	
9-30-80	DRAWN	1-9-30-80

ARKANSAS STATE HIGHWAY COMMISSION


PAVEMENT MARKING DETAILS

STANDARD DRAWING PM-1


NOTE:
 1. UNLESS OTHERWISE SPECIFIED ON THE PLANS, THE UNDERDRAIN COVER SHALL BE THOROUGHLY COMPACTED EARTH AND SHALL BE SUBSIDIARY TO PIPE UNDERDRAIN.
 2. GRANULAR MATERIAL SHALL BE WRAPPED WITH GEOTEXTILE FABRIC, LAP FABRIC 12" OR THE WIDTH OF THE TRENCH AT THE TOP.



PLAN VIEW




SIDE VIEW




DETAIL OF HOLE FOR 4" PIPE

1/4" STAINLESS STEEL BOLT WITH ANCHOR & 1" STAINLESS STEEL WASHER IN APPROX. CENTER OF SCREEN



FRONT VIEW (DETAIL OF RODENT SCREEN)




DETAILS OF PIPE UNDERDRAIN

FERNCO 1056-44 (4" CI/PLASTIC) OR FERNCO 1051-44 (4" AC/DI OR 4" CI/PLASTIC) COUPLING OR EQUAL WITH 2 CLAMPS (TYPICAL)

UNDERDRAIN OUTLET PROTECTORS

FERNCO 1056-44 (4" CI/PLASTIC) OR FERNCO 1051-44 (4" AC/DI OR 4" CI/PLASTIC) COUPLING OR EQUAL WITH 2 CLAMPS (TYPICAL)



NOTE: LATERALS SHALL BE INSTALLED AT ALL SAGS AND AT 250' INTERVALS ON GRADES. THE 250' DISTANCE MAY BE EXCEEDED ONLY WHERE NECESSARY FOR AN ACCEPTABLE OUTLET.

DETAIL OF PIPE UNDERDRAIN LATERALS WHEN PLACED ALONG PAVEMENT EDGE

NOTE: PVC PIPE FOR LATERALS SHALL MEET THE REQUIREMENTS OF ASTM D 1785 (LATEST REVISION) FOR SCHEDULE 40 PIPE.

NOTES FOR PIPE UNDERDRAINS














































- GEOTEXTILE FABRIC SHALL MEET THE REQUIREMENTS OF SECTION 625 FOR TYPE I. PAYMENT FOR GEOTEXTILE FABRIC AND GRANULAR FILTER MATERIAL SHALL BE INCLUDED IN THE PRICE BID PER LIN. FT. FOR "4" PIPE UNDERDRAINS" IN ACCORDANCE WITH SECTION 611 OF THE STANDARD SPECIFICATIONS.
- 4" NON-PERFORATED SCHEDULE 40 PVC PIPE LATERALS WITH OUTLET PROTECTORS SHALL BE INSTALLED AS SHOWN HEREON. LATERALS WILL BE MEASURED AND PAID FOR AS "4" PIPE UNDERDRAINS." UNDERDRAIN OUTLET PROTECTORS WILL BE MEASURED AND PAID FOR BY THE UNIT IN ACCORDANCE WITH SECTION 611 OF THE STANDARD SPECIFICATIONS.
- EXISTING 4" PIPE UNDERDRAINS MAY BE CONNECTED TO PROPOSED DROP INLETS OR EXTENDED WHERE DIRECTED BY THE ENGINEER. PAYMENT FOR CONNECTING TO DROP INLETS SHALL BE CONSIDERED INCLUDED IN THE PRICE BID FOR "4" PIPE UNDERDRAINS."
- THE LOCATION OF ALL LATERALS SHALL BE MARKED WITH 4" X 12" PERMANENT PAVEMENT MARKING TAPE (TYPE III WHITE) AT THE OUTSIDE EDGE OF THE SHOULDER, PLACED TRANSVERSE TO TRAFFIC. PAYMENT FOR THIS WORK SHALL BE INCLUDED IN THE PRICE BID FOR THE VARIOUS CONTRACT ITEMS.
- PAYMENT FOR THE RODENT SCREEN SHALL BE INCLUDED IN THE PRICE BID PER EACH FOR "UNDERDRAIN OUTLET PROTECTORS."
- ANY EXISTING UNDERDRAINS THAT INTERFERE WITH INSTALLATION OF THE NEW UNDERDRAIN SYSTEM SHALL BE REMOVED AND DISPOSED OF AS DIRECTED BY THE ENGINEER. PAYMENT WILL BE CONSIDERED INCLUDED IN THE PRICE BID FOR THE VARIOUS CONTRACT ITEMS. EXISTING UNDERDRAIN OUTLET PROTECTORS SHALL BE REMOVED UNDER THE ITEM "REMOVAL AND DISPOSAL OF UNDERDRAIN OUTLET PROTECTORS."
- AT LOCATIONS WHERE A SINGLE LATERAL IS USED THE CONTRACTOR SHALL HAVE THE FOLLOWING OPTIONS; 1. INSTALL OUTLET PROTECTOR AS SHOWN ON STANDARD DRAWING PU-1 AND GROUT THE UNUSED HOLE OR 2. INSTALL AN OUTLET PROTECTOR WITH A SINGLE HOLE.

12-8-16	ADDED NOTES FOR PIPE UNDERDRAINS, REVISED RODENT SCREEN DETAIL AND NOTES, REMOVED NOTE 1 FOR GRANULAR MATERIAL, ADDED NOTE FOR GEOTEXTILE FABRIC	
4-10-03	REVISED NOTE 3	
1-12-00	REVISED DETAIL OF UNDERDRAIN LATERALS	
11-18-98	REVISED NOTE	
10-18-96	REVISED MIN. DEPTH & GEOTEXTILE FABRIC	
4-26-96	ADDED LATERAL NOTE: 5 1/2" TO 5"	
11-22-95	REVISED LATERALS	
7-20-95	REVISED LATERALS & ADDED NOTE	
11-3-94	REVISED FOR DUAL LATERALS	11-3-94
10-1-92	SUBSTITUTED GEOTEXTILE	10-1-92
8-15-91	ADDED POLYETHYLENE PIPE	8-15-91
11-8-90	DELETED ALTERNATE NOTE	11-8-90
1-25-90	ADDED 4" SNAP ADAPTER	1-25-90
11-30-89	DEL. (SUBGRADE); ADDED (WHERE REQUIRED)	11-30-89
7-15-88	ISSUED P.L.M.	647-7-15-88
DATE	REVISION	DATE FILMED

ARKANSAS STATE HIGHWAY COMMISSION

DETAILS OF PIPE UNDERDRAIN

STANDARD DRAWING PU-1

<p>RI-1</p>  <p>STANDARD 30"x30" EXPRESSWAY 36"x36" SPECIAL 48"x48"</p>	<p>RI-2</p>  <p>STD. 36"x36"x36" EXPWY. 48"x48"x48" FWY. 60"x60"x60"</p>	<p>R2-1</p>  <p>STD. 24"x30" EXPWY. 36"x48" FWY. 48"x60"</p>	<p>W3-5</p>  <p>STD. 36"x36" EXPWY. 48"x48" FWY. 48"x48"</p>	<p>W3-5a</p>  <p>STD. 36"x36" EXPWY. 48"x48" FWY. 48"x48"</p>	<p>R4-1</p>  <p>STD. 24"x30" EXPWY. 36"x48" FWY. 48"x60"</p>	<p>R4-2</p>  <p>STD. 24"x30" EXPWY. 36"x48" FWY. 48"x60"</p>	
<p>R5-1</p>  <p>STD. 30"x30" EXPWY. 36"x36" SPECIAL 48"x48"</p>	<p>R11-2</p>  <p>48"x30"</p>	<p>R11-3A</p>  <p>60"x30"</p>	<p>R11-4</p>  <p>60"x30"</p>	<p>W21-5a</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W1-1</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W1-2</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	
<p>W1-3</p>  <p>STD. 48"x48"</p>	<p>W1-4</p>  <p>STD. 48"x48"</p>	<p>W1-6</p>  <p>STD. 48"x24" SPECIAL 60"x30"</p>	<p>W1-8</p>  <p>STD. 18"x24" SPECIAL 24"x30" EXPWY. 30"x36" FWY. 36"x48"</p>	<p>W3-1</p>  <p>STD. 36"x36" SPECIAL 48"x48"</p>	<p>W3-2</p>  <p>STD. 36"x36" SPECIAL 48"x48"</p>	<p>W4-2</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	
<p>W5-1</p>  <p>STD. 36"x36" SPECIAL 48"x48"</p>	<p>W6-3</p>  <p>EXPWY. 36"x36" SPECIAL 48"x48"</p>	<p>W8-7</p>  <p>EXPWY. 36"x36" FWY. 48"x48"</p>	<p>W9-2</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W13-1</p>  <p>STD. 24"x24"</p>	<p>W20-1</p>  <p>STD. 48"x48"</p>	<p>W20-2</p>  <p>STD. 48"x48"</p>	<p>W20-3</p>  <p>STD. 48"x48"</p>
<p>W20-4</p>  <p>STD. 48"x48"</p>	<p>W20-5</p>  <p>STD. 48"x48"</p>	<p>W20-7a</p>  <p>18" 500 FEET 24" W16-2</p> <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W21-2</p>  <p>STD. 30"x30" SPECIAL 36"x36"</p>	<p>W21-5</p>  <p>STD. 30"x30" SPECIAL 36"x36"</p>	<p>W24-1</p>  <p>STD. 36"x36"</p>	<p>W1-4b</p>  <p>STD. 48"x48"</p>	<p>R56-1</p>  <p>STD. 18"x18"</p>
<p>W8-11</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W8-9</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>G20-1</p>  <p>60"x24"</p>	<p>G20-2</p>  <p>48"x24"</p>	<p>OM-3L OM-3R</p>  <p>12"x36"</p>	<p>M4-9</p>  <p>STD. 30"x24" SPECIAL 48"x36" SPECIAL 60"x48"</p>	<p>M4-10</p>  <p>48"x18"</p>	<p>R55-1</p>  <p>36"x60"</p> <p>• USE 6" C LETTERS •• USE 4" D LETTERS</p>

ADVANCE DISTANCES (XXXX)

500 FT	1/2 MILE
1000 FT	3/4 MILE
1500 FT	1 MILE AHEAD


GENERAL NOTES:

- ALL TRAFFIC CONTROL DEVICES USED ON ROAD CONSTRUCTION SHALL CONFORM TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION, AND TO THE STANDARD HIGHWAY SIGNS, LATEST EDITION, OR AS APPROVED BY THE FEDERAL HIGHWAY ADMINISTRATION.
- TRAFFIC CONTROL DEVICES SHALL BE SET UP JUST BEFORE THE START OF CONSTRUCTION OPERATIONS AND SHALL BE PROPERLY MAINTAINED DURING THE TIME SUCH CONDITIONS EXIST. THEY SHALL REMAIN IN PLACE ONLY AS LONG AS NEEDED AND REMOVED THEREAFTER.
- EXISTING SIGNS AND CONSTRUCTION SIGNS SHALL BE KEPT IN PROPER POSITION, AND BE CLEAN AND LEGIBLE AT ALL TIMES. SIGNS THAT DO NOT APPLY TO EXISTING CONDITIONS SHALL BE REMOVED. SIGNS THAT ARE DAMAGED, DEFACED, OR THAT ACCUMULATE DIRT DURING CONSTRUCTION SHALL BE CLEANED, REPAIRED, OR REPLACED.
- SIGNS ARE USUALLY MOUNTED ON A SINGLE POST, ALTHOUGH THOSE WIDER THAN 36" OR LARGER THAN 10 SQ. FT. SHALL BE MOUNTED ON TWO POSTS OR ABOVE A TYPE III BARRICADE.
- SIGN POSTS DIRECT BURIED IN SOIL SHALL BE 2 LB. MINIMUM CHANNEL POST OR 4"x4" WOOD POSTS. CHANNEL POSTS SHALL BE PAINTED GREEN. WOOD POSTS SHALL BE PAINTED WHITE. ALL POSTS SHALL BE NEATLY CONSTRUCTED, AND SHALL BE REPLUMBED, CLEANED, OR REPAIRED AS NEEDED FOR THE DURATION OF THE JOB. THERE SHALL NOT BE MORE THAN 2 POSTS IN A 7' PATH FOR WOOD OR CHANNEL POSTS. ANY CHANNEL POST SPLICE SHALL BE IN ACCORDANCE WITH STANDARD DRAWING TC-3.
- POST MOUNTED SIGNS IN RURAL AREAS SHALL BE CONSTRUCTED WITH THE NEAR EDGE OF THE SIGN FROM 6 TO 12 FEET FROM THE PAVEMENT EDGE. SIGNS IN URBAN AREAS AND BARRICADE MOUNTED SIGNS SHALL BE MOUNTED A MINIMUM OF 2 FEET FROM THE PAVEMENT EDGE.
- ALL POST AND BARRICADE MOUNTED SIGNS MOUNTED IN URBAN AREAS SHALL BE MOUNTED A MINIMUM DISTANCE OF 7' FROM THE BOTTOM OF THE SIGN TO THE ROADWAY SURFACE. ALL POST AND BARRICADE MOUNTED SIGNS MOUNTED IN RURAL AREAS SHALL BE MOUNTED A MINIMUM DISTANCE OF 7' FROM THE BOTTOM OF THE SIGN TO THE ROADWAY SURFACE, EXCEPT A MINIMUM OF 6' SHALL BE USED WHEN MOUNTING AN ADVISORY SIGN BELOW A WARNING SIGN. TEMPORARY SIGNS MAY BE MOUNTED ON PORTABLE SUPPORTS FOR INTERMEDIATE TERM STATIONARY WORK CONDITIONS. THE SIGNS MINIMUM MOUNTING HEIGHT SHALL BE 5'. RETROREFLECTIVE DEVICES SHALL BE USED. TEMPORARY SIGNS MAY BE MOUNTED ON PORTABLE SUPPORTS FOR SHORT-TERM, SHORT DURATION, AND MOBILE CONDITIONS. THEY SHALL BE NO LESS THAN ONE (1) FOOT ABOVE THE TRAVELED WAY. LONG-TERM STATIONARY SIGNS SHALL BE DIRECT BURIED IN SOIL, UNLESS CONDITIONS NECESSITATE THE USE OF PORTABLE SIGNS, OR AS APPROVED BY THE ENGINEER. CONCRETE PADS, CONCRETE OR ROCK BALLAST, OR OTHER SOLID MATERIALS SHALL NOT BE UTILIZED WITH PORTABLE SIGN SUPPORTS.
- FLAGGERS SHALL USE REFLECTORIZED STOP-SLOW PADDLES. FLAGS MAY BE USED ONLY FOR EMERGENCY SITUATIONS.
- MOST OF THE SIGNS SHOWN ARE ORIENTED TO THE RIGHT. HOWEVER, THIS DOES NOT PRECLUDE THE USE OF MIRROR IMAGES OF THESE SIGNS WHERE THE REVERSE ORIENTATION MIGHT BETTER CONVEY TO MOTORISTS THE PROPER DIRECTION OF MOVEMENT.
- R55-1 SIGNS SHALL BE PLACED AT LEAST 1500' BUT NOT MORE THAN 1 MILE IN ADVANCE OF THE WORK ZONE. IF A SPEED LIMIT REDUCTION IS IN EFFECT, THE SIGN SHALL BE PLACED A MINIMUM OF 500' IN ADVANCE OF THE "REDUCED SPEED AHEAD" SIGN.


• NOTE: SUPPORTS FOR SIGNS, BARRICADES, AND VERTICAL PANELS THAT ARE DIFFERENT FROM THE REQUIREMENTS SHOWN IN NOTES 4 & 5, BUT MEET THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH), WILL BE ACCEPTED. COMPLIANCE WITH THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) IS REQUIRED FOR ALL PROJECTS.

DATE	REVISION	FILMED
11-07-19	REVISED FOR MASH	
4-13-17	DELETED RSP-1 & ADDED W21-5a	
9-2-15	REVISED REDUCED SPEED LIMIT AHEAD SIGNS REVISED ROAD WORK NEXT XX MILES	
12-15-11	REVISED W24-1	
11-17-10	DELETED W8-9a & ADDED W8-9	
10-15-09	ADDED REFERENCE TO MASH & ADDED SIGN W24-1	
4-17-08	REVISED SIGN DESIGNATIONS	
11-18-04	REVISED NOTES	
10-9-03	REVISED NOTE 1	
11-16-01	REVISED NOTE 7	
9-28-00	REVISED NOTE	
11-18-98	ADDED NOTE	
6-26-97	REVISED NOTE 5	
4-03-97	REVISED NOTE 5	
10-18-96	ADDED CONTROLLED ACCESS HWY. SIGN & TO NOTE 7	
10-12-95	ADDED R55-1	
6-8-95	REVISED TO CORRECT SIGN ILLUSTRATIONS	6-8-95
2-2-95	REVISED PER PART VI, MUTCD SEPT. 3, 1993	
8-15-91	DRAWN AND PLACED IN USE	


ARKANSAS STATE HIGHWAY COMMISSION
STANDARD TRAFFIC CONTROLS
FOR HIGHWAY CONSTRUCTION
STANDARD DRAWING TC-1




(A) TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES ON A 2-LANE HIGHWAY WHERE THE ENTIRE ROADWAY IS CLOSED AND A BYPASS DETOUR IS PROVIDED.




(B) TYPICAL APPLICATION - 4-LANE DIVIDED ROADWAY WHERE ONE ROADWAY IS CLOSED.




(C) TYPICAL APPLICATION - 4-LANE UNDIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.



(D) TYPICAL APPLICATION - ROADWAY CLOSED BEYOND DETOUR POINT.




(E) TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES ON 2-LANE HIGHWAY WHERE ONE LANE IS CLOSED AND FLAGGING IS PROVIDED.



(F) TYPICAL APPLICATION - 4-LANE UNDIVIDED ROADWAY WITH INSIDE LANE CLOSED.

- KEY:
- FLAGGER
 - POSITIVE BARRIER
 - ARROW PANEL (IF REQUIRED)
 - TYPE III BARRICADE
 - CHANNELIZING DEVICE
 - TRAFFIC DRUM
 - RAISED PAVEMENT MARKER



TYPICAL ADVANCE WARNING SIGN PLACEMENT

TAPER FORMULAE:

$L = SXW$ FOR SPEEDS OF 45MPH OR MORE.

$L = \frac{WS^2}{60}$ FOR SPEEDS OF 40MPH OR LESS.

WHERE:

L = MINIMUM LENGTH OF TAPER.

S = NUMERICAL VALUE OF POSTED SPEED LIMIT PRIOR TO WORK OR 85TH PERCENTILE SPEED.


W = WIDTH OF OFFSET.

GENERAL NOTES:


1. THE MAINTENANCE DIVISION SHALL CONDUCT A BALL BANK STUDY TO DETERMINE THE ADVISORY SPEED LIMIT PRIOR TO OPENING TO TRAFFIC. THE ADVISORY SPEED WILL BE POSTED ON W1-3 OR W1-4 CURVE WARNING SIGNS. USE W1-4 WHEN SPEED IS GREATER THAN 30MPH AND W1-3 WHEN 30MPH OR LESS.
2. WHEN THE EXISTING SPEED LIMIT IS 55MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 45MPH, THE R2-1(55) SHALL BE OMITTED AND THE W3-5 SHALL BE INSTALLED AT THAT LOCATION. ADDITIONAL R2-1(45)MPH SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(XX) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
3. WHEN THE EXISTING SPEED LIMIT IS 65MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 55MPH, THE R2-1(65) SHALL BE OMITTED. ADDITIONAL R2-1(55)MPH SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(XX) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
4. THE MAXIMUM SPACING BETWEEN CHANNELIZING DEVICES IN A TAPER SHOULD BE APPROXIMATELY EQUAL IN FEET TO THE SPEED LIMIT. BEYOND THE TAPER, MAXIMUM SPACING SHALL BE TWO TIMES THE SPEED LIMIT, OR AS DIRECTED BY THE ENGINEER.
5. WARNING LIGHTS AND/OR FLAGS MAY BE MOUNTED TO SIGNS OR CHANNELIZING DEVICES AT NIGHT AS NEEDED.
6. PAVEMENT MARKINGS NO LONGER APPLICABLE WHICH MIGHT CREATE CONFUSION IN THE MINDS OF VEHICLE OPERATORS SHALL BE REMOVED OR OBLITERATED AS SOON AS PRACTICABLE.
7. TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL BE DELINEATED BY AFFIXING CONSPICUITY MATERIAL IN A CONTINUOUS LINE ON THE FACE OF THE TRAILER. WHEN PLACED ON OR ADJACENT TO THE SHOULDER AND NOT BEHIND A POSITIVE BARRIER, THESE DEVICES SHALL BE DELINEATED BY PLACING FIVE (5) TRAFFIC DRUMS, EQUALLY SPACED ALONG THE TRAFFIC SIDE OF THE DEVICE. PAYMENT FOR TRAFFIC DRUMS SHALL BE CONSIDERED INCLUDED IN THE PRICE BID FOR VARIOUS TRAILER MOUNTED DEVICES.
8. DIMENSIONS SHOWN FOR RAISED PAVEMENT MARKERS ARE TYPICAL. THE CONTRACTOR MAY SUBSTITUTE SIMILAR MARKERS WITH THE APPROVAL OF THE ENGINEER. REQUESTING APPROVAL FOR SIMILAR MARKERS MAY BE MADE BY REFERRING TO THE ARDOT QUALIFIED PRODUCTS LIST.
9. ALL TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL MEET THE REQUIREMENTS OF THE MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).

DATE	REVISION	FILED
05-20-21	REVISED NOTE 7	
11-07-19	REVISED NOTE 1, ADDED NOTE 9	
9-2-15	REVISED NOTE 2, ADDED NOTE 8, REVISED DRAWING (A) & REPLACED R2-5A WITH W3-5	
9-12-13	REVISED DETAIL OF RAISED PAVEMENT MARKERS	
3-11-10	ADDED (AFAD)	
11-20-08	REVISED SIGN DESIGNATIONS	
11-18-04	ADDED GENERAL NOTE	
10-18-96	ADDED R55-1	
4-26-96	CORRECTED (a) BEHIND G20-2	
6-8-95	CORRECTED SIGN IDENT. ON W1-4A	6-8-95
2-2-95	REVISED PER PART VI, MUTCD, SEPT. 3, 1993	
8-15-91	DRAWN AND PLACED IN USE	

ARKANSAS STATE HIGHWAY COMMISSION
STANDARD TRAFFIC CONTROLS
FOR HIGHWAY CONSTRUCTION





(A) TYPICAL APPLICATION - DAYTIME MAINTENANCE OPERATIONS OF SHORT DURATION ON A 4-LANE DIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.





(B) TYPICAL APPLICATION - 3-LANE ONEWAY ROADWAY WHERE CENTER LANE IS CLOSED.


CHANNELIZING DEVICES



NOTE: FOR ALL ROAD CLOSURES, THE TYPE III BARRICADES SHALL BE OF SUFFICIENT LENGTH TO EXTEND ACROSS ENTIRE ROADWAY.



- KEY:
- ARROW PANEL (IF REQUIRED)
 - CHANNELIZING DEVICE
 - TRAFFIC DRUM
- GENERAL NOTES:
1. A SPEED LIMIT REDUCTION MAY BE IMPLEMENTED ONLY WHEN DESIGNATED IN THE PLAN OR WHEN RECOMMENDED BY THE ROADWAY DESIGN DIVISION.
 2. WHEN THE EXISTING SPEED LIMIT IS 55MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 45MPH, THE R2-1(55) SHALL BE OMITTED AND THE W3-5 SHALL BE INSTALLED AT THAT LOCATION. ADDITIONAL R2-1(45)MPH SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1/2 MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(XX) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
 3. WHEN THE EXISTING SPEED LIMIT IS 65MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 55MPH, THE R2-1(65) SHALL BE OMITTED. ADDITIONAL R2-1(55)MPH SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1/2 MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(XX) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
 4. THE MAXIMUM SPACING BETWEEN CHANNELIZING DEVICES IN A TAPER SHOULD BE APPROXIMATELY EQUAL IN FEET TO THE SPEED LIMIT. BEYOND THE TAPER, MAXIMUM SPACING SHALL BE TWO TIMES THE SPEED LIMIT OR AS DIRECTED BY THE ENGINEER.
 5. WARNING LIGHTS AND/OR FLAGS MAY BE MOUNTED TO SIGNS OR CHANNELIZING DEVICES AT NIGHT AS NEEDED.
 6. PAVEMENT MARKINGS NO LONGER APPLICABLE WHICH MIGHT CREATE CONFUSION IN THE MINDS OF VEHICLE OPERATORS SHOULD BE REMOVED OR OBLITERATED AS SOON AS PRACTICABLE.
 7. THE G20-1 SIGN WILL BE REQUIRED ON JOBS OF OVER TWO MILES IN LENGTH. WHEN THE LANE CLOSURE IS NOT AT THE BEGINNING OF THE PROJECT, THE G20-1 SIGN SHALL BE ERECTED 125' IN ADVANCE OF THE JOB LIMIT. ADDITIONAL W20-1(1/2 MILE) SIGNS ARE NOT REQUIRED IN ADVANCE OF LANE CLOSURES THAT BEGIN INSIDE THE PROJECT LIMITS.
 8. FLAGGERS SHALL USE STOP/SLOW PADDLES FOR CONTROLLING TRAFFIC THROUGH WORK ZONES. FLAGS MAY BE USED ONLY FOR EMERGENCY SITUATIONS.
 9. ALL PLASTIC DRUMS AND CONES SHALL MEET THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).
 10. TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL BE DELINEATED BY AFFIXING CONSPICUITY MATERIAL IN A CONTINUOUS LINE ON THE FACE OF THE TRAILER. WHEN PLACED ON OR ADJACENT TO THE SHOULDER AND NOT BEHIND A POSITIVE BARRIER, THESE DEVICES SHALL BE DELINEATED BY PLACING FIVE (5) TRAFFIC DRUMS, EQUALLY SPACED ALONG THE TRAFFIC SIDE OF THE DEVICE. PAYMENT FOR TRAFFIC DRUMS SHALL BE CONSIDERED INCLUDED IN THE PRICE BID FOR VARIOUS TRAILER MOUNTED DEVICES.
 11. ALL TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL MEET THE REQUIREMENTS OF THE MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).




(C) TYPICAL APPLICATION - CONSTRUCTION OPERATIONS OF INTERMEDIATE TO LONG TERM DURATION ON A 4-LANE DIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.

TRAFFIC CONTROL DEVICES			
NON-INTERSTATE			
VERTICAL DIFFERENTIAL	LOCATION	TRAFFIC CONTROL	
		≤ 45 MPH	> 45 MPH
≤ 1"	CENTERLINE	W8-11	W8-11
> 1" - 3"	CENTERLINE	W8-11 AND CENTERLINE LANE STRIPING	W8-11 AND CENTERLINE LANE STRIPING
> 3"	CENTERLINE	STANDARD LANE CLOSURE(6)	STANDARD LANE CLOSURE(6)
≤ 3"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-9 AND TRAFFIC DRUMS(1)	W8-9 AND TRAFFIC DRUMS(1)
> 3"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS(1)	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS(1)
> 6"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS(1)	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS(2)
> 18"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS(1)	A STABILIZED WEDGE, W8-17, EDGE LINE STRIPING AND TRAFFIC DRUMS(3)
> 24"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	PRECAST CONCRETE BARRIER(4) & EDGE LINES	PRECAST CONCRETE BARRIER(4) & EDGE LINES

INTERSTATE		
VERTICAL DIFFERENTIAL	LOCATION	TRAFFIC CONTROL
≤ 3"	CENTERLINE	W8-11 AND LANE STRIPING
≤ 3"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-9, EDGE LINE STRIPING, AND TRAFFIC DRUMS(2)
> 3"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS(2)
> 6"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	PRECAST CONCRETE BARRIER & EDGE LINES


INTERSTATE AND NON-INTERSTATE		
FORESLOPE	HEIGHT	TRAFFIC CONTROL
1:1	> 2 FT	PRECAST CONCRETE BARRIER
2:1	≤ 5 FT	TRAFFIC DRUMS
2:1	> 5 FT	PRECAST CONCRETE BARRIER
Flatter than 2:1	N/A	TRAFFIC DRUMS

- GENERAL NOTES:
1. WHEN THE SHOULDER AREA IS USED AS PART OF THE TRAVELED LANE AND THERE IS INSUFFICIENT WIDTH TO PLACE TRAFFIC DRUMS ON THE REMAINING SHOULDER WIDTH, THEN VERTICAL PANELS SHALL BE USED.
 2. WHEN THERE IS INSUFFICIENT WIDTH TO PLACE TRAFFIC DRUMS ON THE REMAINING SHOULDER WIDTH, A STABILIZED WEDGE SHALL BE USED.
 3. PRECAST CONCRETE BARRIER WALL CAN BE USED IN LIEU OF A STABILIZED WEDGE, W8-17 SIGN, EDGE LINE STRIPING, AND TRAFFIC DRUMS, IF AND WHERE DIRECTED BY THE ENGINEER.
 4. A STABILIZED WEDGE, W8-17 SIGN, EDGE LINE STRIPING, AND TRAFFIC DRUMS CAN BE USED IN LIEU OF PRECAST CONCRETE BARRIER WALL, IF AND WHERE DIRECTED BY THE ENGINEER.
 5. W21-5, W21-50, AND/OR W21-50b SIGNS SHALL BE USED WHERE THE ROADWAY IS UNOBSTRUCTED IF AND WHERE DIRECTED BY THE ENGINEER. TIME LIMITATIONS MUST CONFORM TO SECTION 603 OF THE STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION).




STABILIZED WEDGE

NOTE: MATERIALS FOR THE STABILIZED WEDGE SHALL MEET THE REQUIREMENTS PROVIDED IN SECTION 603.02 OF THE STANDARD SPECIFICATIONS.










(D) TYPICAL APPLICATION - CLOSING MULTIPLE LANES OF A MULTILANE HIGHWAY.





DATE	REVISION	FILED
08-12-21	REVISED TRAFFIC CONTROL DEVICES AND NOTES	
05-20-21	REVISED NOTE 10	
2-27-20	REVISED TRAFFIC CONTROL DEVICES DETAILS	
11-07-19	REVISED NOTE 9, ADDED NOTE II	
7-25-19	REVISED TRAFFIC CONTROL DEVICES DETAILS	
9-2-15	REVISED NOTE 2 & REPLACED R2-5A WITH W3-5	
10-15-09	ADDED REFERENCE TO MASH	
11-20-08	REVISED SIGN DESIGNATIONS	
11-18-04	ADDED NOTE	
10-1-98	ADDED NOTE	
4-03-97	ADDED (SP) TO W6-1& REVISED TRAFFIC CONTROL DEVICES NOTE	
10-18-96	ADDED R55-1	
10-12-95	MOVED UPPER SPLICE	
6-8-95	REVISED SPLICE DETAIL, TEXT	6-8-95
2-2-95	REVISED PER PART VI, MUTCD, SEPT. 3, 1993	
8-15-91	DRAWN AND PLACED IN USE	

REINFORCING BAR TABLE PER BARRIER UNIT			
MARK	LOCATION	BAR SIZE (NO. BARS)	SKETCH
H-1	HORIZONTAL IN BARRIER TIED INSIDE V-1 BARS	#5 (6)	19'-3"
H-2	CENTERED ABOVE DRAIN SLOTS LONG. & TRANSVERSELY	#5 (6)	6'-6"
H-3	TIED ABOVE H-1 BARS TO SUPPORT H-2, TIED TO V-1	#4 (2)	1'-6"
S-1	OVER LIFT HOLES	#4 (2)	2'-5" 3/8" R 90°
S-2	HORIZ. AROUND SLOTS BETWEEN V-1'S & DRAIN SLOTS	#4 (2)	1 1/2" R SLOTS 1" MIN. CLEAR TO BAR 5'-1" BAR W/ (4) 1 1/2" R BENDS & MIN. 1'-0" OVERLAP
V-1	VERTICAL IN BARRIER (3) EACH END & (2) AT EACH DRAIN SLOTS	#5 (16)	TOTAL LENGTH 4'-9" 2 3/16" R 12° 4 3/8" 2'-1 3/8" 3/8"




BARRIER STABILIZATION DETAIL ROADWAY SECTION
 (E) 4" - CONCRETE PAVEMENT
 8" - ASPHALT PAVEMENT
 12" - SHOULDER AREAS



NOTE: THREADED INSERTS SHALL BE CAST IN PLACE FOR ALL NEW BRIDGE DECKS AND DRILLED AND GROUDED FOR EXISTING BRIDGE DECKS. INSERTS SHALL HAVE A MINIMUM ULTIMATE LOAD CAPACITY OF 8000 LBS. IN TENSION. AFTER REMOVAL OF BARRIER, BOLTS, AND ANGLES, THE INSERTS SHALL BE FILLED WITH APPROVED NON-SHRINK EPOXY.

BARRIER STABILIZATION DETAIL BRIDGE DECKS



- GENERAL NOTES**
- THE CONTRACTOR SHALL FURNISH THE PRECAST CONCRETE BARRIER UNITS AND SHALL BE RESPONSIBLE FOR THE MANUFACTURE, SHIPMENT, STORAGE, PLACEMENT AND REMOVAL. AT THE COMPLETION OF THE PROJECT, THE PRECAST UNITS WILL REMAIN THE PROPERTY OF THE CONTRACTOR.
 - MATERIALS SHALL MEET THE FOLLOWING MINIMUM REQUIREMENTS:
 CONCRETE: 2500 PSI COMPRESSIVE STRENGTH AT 28 DAYS.
 REINFORCING STEEL: AASHTO M 31 OR M 53, GRADE 60
 STRUCTURAL STEEL: AASHTO-M270 GRADE 36 SHALL BE USED FOR THE CONNECTION PIN, CONNECTION LOOPS, AND STABILIZATION PINS. A ONE PIECE PIN WITH A 3" ROUNDED TOP MAY BE USED IN PLACE OF THE DETAILED CONNECTION PIN.
 DELINEATORS: DELINEATORS SHALL BE MOUNTED AT 10' SPACING ON TOP OF PRECAST BARRIER.
 IN APPLICATIONS WHERE BARRIER WALL IS WITHIN 6 FEET OF A TRAFFIC LANE, ADDITIONAL DELINEATORS SHALL BE PLACED ON THE BARRIER AT 10' SPACING APPROXIMATELY ONE (1) FOOT FROM THE TOP OF THE BARRIER. DELINEATORS SHALL BE ON THE ARDOT QUALIFIED PRODUCTS LIST FOR CONSTRUCTION CONCRETE BARRIER MARKERS. DELINEATOR COLOR SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES. PAYMENT FOR DELINEATORS SHALL BE CONSIDERED INCLUDED IN THE PRICE BID PER LIN. FT. FOR "FURNISHING AND INSTALLING PRECAST CONCRETE BARRIER". THE CONTRACTOR SHALL CERTIFY TO THE ENGINEER THAT THE MATERIAL AND THE DESIGN USED IN THE PRECAST BARRIER UNITS MEETS THE REQUIREMENTS AS SHOWN ON THIS STANDARD DRAWING.
 - OTHER PRECAST CONCRETE BARRIERS THAT HAVE BEEN CRASH TESTED AND APPROVED BY THE FEDERAL HIGHWAY ADMINISTRATION TO MEET THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) WILL BE ACCEPTED OR AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL FURNISH A CERTIFICATION OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) COMPLIANCE FOR ANY OTHER TYPES OF PRECAST BARRIER TO BE USED. THE CERTIFICATION SHALL STATE THAT THE PRECAST CONCRETE BARRIER MEETS THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH). MIXING OF SHAPES WILL NOT BE ALLOWED IN A CONTINUOUS LINE OF UNITS.
 - DOWEL HOLES IN PAVEMENT OR BRIDGE SLABS THAT ARE TO REMAIN IN PLACE SHALL BE FILLED. HOLES IN CONCRETE PAVEMENT AND BRIDGE SLABS SHALL BE FILLED WITH AN APPROVED NON-SHRINK EPOXY GROUT. HOLES IN ASPHALT PAVEMENT SHALL BE FILLED WITH AN APPROVED ASPHALT JOINT FILLER. PAYMENT FOR DRILLING AND FILLING HOLES TO BE INCLUDED IN THE PRICE FOR VARIOUS BARRIER ITEMS.
 - ATTACH UNITS TO ROADWAY SURFACE WITH STABILIZATION PINS AND TO DECK SLABS USING BOLTS WHEN REQUIRED.
 - A 4" WHITE PVC SLEEVE MAY BE USED TO FORM THE LIFTING HOLE AND IF USED THE SLEEVE IS TO BE LEFT IN PLACE.


11-07-19	REVISED NOTE 3	
2-27-14	REVISED BARRIER STABILIZATION DETAIL	
10-15-09	ADDED REFERENCE TO MASH	
8-5-09	REV. NOTE 3 CONCERNING DRAIN SLOTS	
11-29-07	REVISED NOTE 3	
5-25-06	DELETED GENERAL NOTE 7	
11-18-04	REVISED BARRIER STABILIZATION DETAIL BRIDGE DECKS	
4-10-03	REVISED GENERAL NOTE 2	
8-22-02	ISSUED NEW DRAWING	
DATE	REVISION	FILMED

ARKANSAS STATE HIGHWAY COMMISSION

STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION - TEMPORARY PRECAST BARRIER

STANDARD DRAWING TC-4


(A) 4 feet or greater preferred. If less than 4 feet, Precast Units shall be connected to slab (SEE BARRIER STABILIZATION DETAIL-BRIDGE DECKS STD. DRWG. TC-4)



BARRIER PLACEMENT ALONG BRIDGE WITH OFFSET


No Scale

** Offset Distance for Two Way Traffic Only



SECTION J-J

No Scale



BARRIER PLACEMENT ALONG ROADWAY WITH OFFSET

No Scale


* Offset Distance (See Table)

** Offset Distance For Two Way Traffic Only

Offset Distance Table

Speed (MPH)	Offset Distance (FT.)
≤ 45	12
> 45	18

If offset distance is not attainable, then see 'Barrier Placement With Attenuator' Detail shown below.




SPECIAL END UNIT

No Scale

General Notes

When shown on the Plans, the ends of the Temporary Precast Concrete Barrier shall be protected with a Manual For Assessing Safety Hardware (MASH) approved Crash Cushion. Payment for Crash Cushions shall be made under the item of "Temporary Impact Attenuation Barrier."



BARRIER PLACEMENT WITH ATTENUATOR

No Scale

** Offset Distance For Two Way Traffic Only

*** Min. 3'-0" From Edge of Travel Lane to Nearest Edge of Attenuator

DATE	REVISION	FILMED
11-07-19	REVISED NOTE	
10-15-09	ADDED REFERENCE TO MASH	
5-25-06	REVISED BARRIER PLACEMENT	
8-22-02	ISSUED NEW DRAWING	


ARKANSAS STATE HIGHWAY COMMISSION

**STANDARD TRAFFIC CONTROLS
FOR HIGHWAY CONSTRUCTION -
TEMPORARY PRECAST BARRIER**

STANDARD DRAWING TC-5


GENERAL NOTES

INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO BOTTOM OF DITCH.




WATTLE DITCH CHECK (E-1)

NUMBER OF SAND BAGS AND ARRANGEMENT VARIABLE WITH ON-SITE CONDITIONS. PLACE SAND BAGS AT BASE OF DITCH CHECK IN AREA OF OVERFLOW.




SAND BAG DITCH CHECK (E-5)




ROCK DITCH CHECK (E-6)


GENERAL NOTES
 GEOTEXTILE FABRIC (TYPE 4) IN ACCORDANCE WITH SECTION 625
 GEOTEXTILE FABRIC SHALL BE SPLICED TOGETHER WITH A SEWN SEAM ONLY AT A SUPPORT POST OR TWO SECTIONS OF FENCE MAY BE OVERLAPPED INSTEAD. PAYMENT OF ADDITIONAL MATERIAL FOR OVERLAP WILL NOT BE MADE.



SILT FENCE (E-11)




DROP INLET SILT FENCE (E-7)




SILT FENCE ON R/W FENCE (E-4)

GENERAL NOTES
 1. STRAW BALES SHALL BE INSTALLED SO THAT THE BINDINGS ARE ORIENTED AROUND THE SIDES RATHER THAN ALONG THE TOPS AND BOTTOMS OF THE BALES. THE BALES SHALL BE A MINIMUM OF 30 INCHES IN LENGTH.
 2. NO GAPS SHALL BE LEFT BETWEEN BALES.
 3. BALED STRAW FILTER BARRIERS COMPLETED AND ACCEPTED WILL BE MEASURED BY THE BALE IN PLACE AS AUTHORIZED BY THE ENGINEER AND WILL BE PAID FOR AT THE CONTRACT UNIT PRICE BID PER BALE FOR BALED STRAW DITCH CHECKS.




BALED STRAW FILTER BARRIER (E-2)



FILTER SOCK ALONG SLOPE (E-3)

NOTES:
 1. FILTER SOCKS CAN BE PLACED AT THE TOP, ON THE FACE, AND AT THE TOE OF SLOPES AS SEDIMENT-TRAPPING DEVICES FOR SHEET FLOW RUNOFF.
 2. FILTER SOCKS ARE TYPICALLY SUPPLIED AND INSTALLED WITH 18 INCH DIAMETERS. DIAMETER TOLERANCE IS 2 INCHES, AS FILTER SOCKS TEND TO FLATTEN OUT WHEN PLACED.
 3. STEEL POSTS MAY BE USED AND SHALL BE ROLLED FROM HIGH CARBON STEEL AND HAVE A MINIMUM OF 1.25 LB./FT. POSTS SHALL BE HOT-DIPPED GALVANIZED OR PAINTED WITH HIGH-GRADE WEATHER RESISTANT BROWN OR BLACK STEEL PAINT. STEEL POSTS SHALL BE EQUIPPED WITH ANCHOR PLATE HAVING A MINIMUM AREA OF 14 SQUARE INCHES. POSTS SHALL BE STUDDED, EMBOSSED, OR PUNCHED. POSTS AND ANCHOR PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A702. NO ADDITIONAL PAYMENT WILL BE PROVIDED FOR STEEL POSTS, BUT PRICE WILL BE CONSIDERED SUBSIDIARY TO "FILTER SOCK (18")."
 4. FILTER SOCKS MAY BE UP TO 250 FEET LONG. WHEN USED ON LONG SLOPES, FILTER SOCKS MAY BE JOINTED OR STAGGERED AS SHOWN IN DETAILS.
 5. INSPECT FILTER SOCKS AFTER EACH RUNOFF EVENT. REMOVE AND REPLACE IF SIGNS OF UNDERCUTTING OR DOWNSTREAM RILLS ARE OBSERVED.



COMPOST FILTER SOCK DROP INLET PROTECTION (E-13)

NOTES:
 1. OVERLAP ENDS OF SOCK (1' MIN. 3' MAX.).
 2. USE 18" DIA. SOCK IN NON-TRAFFIC AREAS OR AREAS WHERE SAFETY IS NOT A CONCERN.

DATE	REVISION
11-16-17	ADDED FILTER SOCK E-3 AND E-13
12-15-11	DELETED BALED STRAW DITCH CHECK & ADDED WATTLE DITCH CHECK
11-18-98	ADDED NOTES
07-02-98	ADDED BALED STRAW FILTER BARRIER (E-2)
07-20-95	REVISED SILT FENCE E-4 AND E-11
07-15-94	REV. E-4 & E-11 MIN. 13" BURIED END OF FABRIC
06-02-94	REVISED E-1, 4, 7 & 11; DELETED E-2 & 3
04-01-93	REDRAWN
10-01-92	REDRAWN
08-02-76	ISSUED R.D.M.


ARKANSAS STATE HIGHWAY COMMISSION
 TEMPORARY EROSION CONTROL DEVICES
 STANDARD DRAWING TEC-1

CLEARING AND GRUBBING

CONSTRUCTION SEQUENCE

1. PLACE PERIMETER CONTROLS (I.E. SILT FENCES, DIVERSION DITCHES, SEDIMENT BASINS, ETC.)
2. PERFORM CLEARING AND GRUBBING OPERATION.

EXCAVATION



NOTE:
NUMBER OF PHASES WILL VARY.
THREE PHASES SHOWN FOR
ILLUSTRATION.


GENERAL NOTE

ALL CUT SLOPES SHALL BE DRESSED, PREPARED, SEEDED, AND MULCHED AS THE WORK PROGRESSES. SLOPES SHALL BE EXCAVATED AND STABILIZED IN EQUAL INCREMENTS NOT TO EXCEED 25 FEET, MEASURED VERTICALLY.

CONSTRUCTION SEQUENCE

1. EXCAVATE AND STABILIZE INTERCEPTOR AND/OR DIVERSION DITCHES.
2. PERFORM PHASE 1 EXCAVATION. PLACE PERMANENT OR TEMPORARY SEEDING.
3. PERFORM PHASE 2 EXCAVATION. PLACE PERMANENT OR TEMPORARY SEEDING.
4. PERFORM FINAL PHASE OF EXCAVATION. PLACE PERMANENT OR TEMPORARY SEEDING. STABILIZE DITCHES. CONSTRUCT DITCH CHECKS, DIVERSION DITCHES, SEDIMENT BASINS, OR OTHER EROSION CONTROL DEVICES AS REQUIRED.

EMBANKMENT



NOTE:
NUMBER OF PHASES WILL VARY.
THREE PHASES SHOWN FOR
ILLUSTRATION.

GENERAL NOTE

ALL EMBANKMENT SLOPES SHALL BE DRESSED, PREPARED, SEEDED, AND MULCHED AS THE WORK PROGRESSES. SLOPES SHALL BE CONSTRUCTED AND STABILIZED IN EQUAL INCREMENTS NOT TO EXCEED 25 FEET, MEASURED VERTICALLY.

CONSTRUCTION SEQUENCE

1. CONSTRUCT DIVERSION DITCHES, DITCH CHECKS, SEDIMENT BASINS, SILT FENCES, OR OTHER EROSION CONTROL DEVICES AS SPECIFIED.
2. PLACE PHASE 1 EMBANKMENT WITH PERMANENT OR TEMPORARY SEEDING. PROVIDE DIVERSION DITCHES AND SLOPE DRAINS IF EMBANKMENT CONSTRUCTION IS TO BE TEMPORARILY ABANDONED FOR A PERIOD OF GREATER THAN 21 DAYS.
3. PLACE PHASE 2 EMBANKMENT WITH PERMANENT OR TEMPORARY SEEDING. PROVIDE DIVERSION DITCHES AND SLOPE DRAINS IF EMBANKMENT CONSTRUCTION IS TO BE TEMPORARILY ABANDONED FOR A PERIOD OF GREATER THAN 21 DAYS.
4. PLACE FINAL PHASE OF EMBANKMENT WITH PERMANENT OR TEMPORARY SEEDING. PLACE DIVERSION DITCHES AND SLOPE DRAINS AND MAINTAIN UNTIL ENTIRE SLOPE IS STABILIZED.

			ARKANSAS STATE HIGHWAY COMMISSION
			TEMPORARY EROSION CONTROL DEVICES
11-03-94	CORRECTED SPELLING		
6-2-94	Drawn & Issued		6-2-94
DATE	REVISION		FILMED
			STANDARD DRAWING TEC-3